



## FarBo® Overflow insert

Overflow insert for roof drainage systems

### Application

- Used in conjunction with FarBo roof outlets to provide an overflow roof drainage system

### Key Features

- Manufactured from high quality 316 grade stainless steel
- Includes EPDM O-ring for ultimate waterproof seal
- Used in conjunction with FarBo® roof outlets to provide overflow by increasing the drainage height to 25/35mm above the level

## Datasheet

Document Reference: DS-RDS-OI-6.24/02

03 ROOF DRAINAGE SYSTEMS  
FarBo® Overflow insert

# FarBo® Overflow insert

Code	To suit outlet diameter (mm)	Overflow height (mm)
FO-OF-75	75	25 or 35
FO-OF-90	90	
FO-OF-110	110	
FO-OF-125	125	
FO-OF-160	160	



**FO-OF**

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY  
T: 0845 450 4783 | F: 0845 450 7486 | E: [info@fixfast.com](mailto:info@fixfast.com) | W: [www.fixfast.com](http://www.fixfast.com)

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.  
The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

© Fixfast July 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice



Certificate Number 10905  
ISO 9001:2008  
ISO 14001:2004  
BS OHSAS 18001:2007