

ProtectorFast™

Stainless steel security fasteners

Application

- Tamper deterrent self-tapping fastener

Key Features

- A2/304 stainless steel for optimum corrosion resistance
- Pan and CSK heads available
- Secure drive type, can only be removed using the matched drive bit (Refer to Bit holders and Drive bits datasheet in Specialist Tools section)


Datasheet

Document Reference: [DS-FS-PF-7.17/01](#)

01 FASTENER SYSTEMS
ProtectorFast™ Stainless
steel security fasteners

ProtectorFast™ Stainless steel security fasteners

Code	Diameter (mm)	Length (mm)	Drive bit	Boxed In
SEC-CST-SS-4.2 x 19	4.2	19	T-PIN 20	100
SEC-CST-SS-4.2 x 25	4.2	25	T-PIN 20	100
SEC-CST-SS-4.2 x 38	4.2	38	T-PIN 20	100
SEC-CST-SS-4.2 x 50	4.2	50	T-PIN 20	100
SEC-CST-SS-4.8 x 19	4.8	19	T-PIN 25	100
SEC-CST-SS-4.8 x 25	4.8	25	T-PIN 25	100
SEC-CST-SS-4.8 x 38	4.8	38	T-PIN 25	100
SEC-CST-SS-4.8 x 50	4.8	50	T-PIN 25	100
SEC-CST-SS-5.5 x 25	5.5	25	T-PIN 27	100
SEC-CST-SS-5.5 x 38	5.5	38	T-PIN 27	100
SEC-CST-SS-5.5 x 50	5.5	50	T-PIN 27	100
SEC-CST-SS-6.3 x 50	6.3	50	T-PIN 30	100



SEC-CST-SS

Code	Diameter (mm)	Length (mm)	Drive bit	Boxed In
SEC-PST-SS-4.2 x 19	4.2	19	T-PIN 15	100
SEC-PST-SS-4.2 x 25	4.2	25	T-PIN 15	100
SEC-PST-SS-4.2 x 38	4.2	38	T-PIN 15	100
SEC-PST-SS-4.2 x 50	4.2	50	T-PIN 15	100
SEC-PST-SS-4.8 x 19	4.8	19	T-PIN 25	100
SEC-PST-SS-4.8 x 25	4.8	25	T-PIN 25	100
SEC-PST-SS-4.8 x 38	4.8	38	T-PIN 25	100
SEC-PST-SS-4.8 x 50	4.8	50	T-PIN 25	100
SEC-PST-SS-5.5 x 25	5.5	25	T-PIN 27	100
SEC-PST-SS-5.5 x 38	5.5	38	T-PIN 27	100
SEC-PST-SS-5.5 x 50	5.5	50	T-PIN 27	100
SEC-PST-SS-6.3 x 50	6.3	50	T-PIN 30	100



SEC-PST-SS

Pilot hole size chart – For self-tapping screws into metal

Metal thickness (mm)	Fastener diameter (mm)		
	4.2	4.8	5.5
up to 1.0	3.0 - 3.2	3.6 - 3.8	4.0 - 4.2
1.0 - 2.0	3.2 - 3.4	3.6 - 3.8	4.2 - 4.4
2.0 - 3.0	3.4 - 3.8	4.0 - 4.2	4.4 - 4.8
over 3.0	3.8 - 3.9	4.2 - 4.4	4.8 - 5.1
Pilot hole diameter (mm)			

These figures are given for guidance only and may vary with application. Please check your application first. Stainless steel self-tapping screws are only recommended for use in metal up to 3mm thick.

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.

The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007