



StrikeClip[™]

Lightning clips

Application

For securing lightning conductor tape for roof and wall applications

Key Features

- Unique recessed rivet to eliminate damage to the membrane
- Manufactured from high quality polymer, with excellent UV repellent properties to prevent them fading and going brittle in the sun's rays
- Easy to use supplied as one piece product
- Accommodate a conductor tape up to 27mm wide x 5mm thick.
- Supplied with either 100mm x 100mm membrane flange or 70mm diameter semi-rigid PVC base

Datasheet

04 ROOFTOP DRAINAGE StrikeClip™ Lightning clips

StrikeClip™ Lightning clips

Code	Flange description	Flange size (mm)	Suggested fixing centres (mm)
LC-ROUND	Semi rigid PVC	70 diameter	500
LC-ROUND-SA	As above with self-adhesive	70 diameter	500
LC-SBS-CHARCOAL	Felt - charcoal	100 x 100	500
LC-SBS-BRINDLE	Felt - brindle	100 x 100	500
LC-PVC-LT GREY	PVC - light grey	100 x 100	500
LC-PVC-DK GREY	PVC - dark grey	100 x 100	500
LC *	N/A		1000 **

Please contact our sales office for bespoke requirements.

Please apply pressure with a seam roller once installed to activate the bond.



LC-ROUND



LC-SBS-CHARCOAL

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY T: 0800 304 7616 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com



^{*}LC type is suitable for vertical applications only as it has no membrane flange.

^{**} up to 20m from ground level - 500mm thereafter - IEC 62305 standard.