

# RyMar® Vent Pipe Cover - Insertion Model



## Application

The vent pipe cover is used for the flashing of soil pipes which penetrate the roof construction and the roofing membrane

## Key Features

Manufactured from high quality stainless steel

A vent cover model for use with insertion-type soil pipes

Provides a flashing & extension of the soil pipe above the roof

Can be supplied with flange either for bituminous or synthetic roofing membranes, or liquid applied systems

## RyMar® Vent pipe covers - insertion model

Product Code	Pipe diameters (mm)	O-ring seal diameter (mm)	Membrane attachment	To suit vent pipe OD (mm)	To suit vent pipe ID (mm)
RM-IMVENT-75-SBS	63	10	Bituminous	75	70-79
RM-IMVENT-110-SBS	90			110	96-106
RM-IMVENT-160-SBS	145	5	Light grey PVC	160	150-153
RM-IMVENT-75-PVC LT GREY	63	10		75	70-79
RM-IMVENT-110-PVC LT GREY	90			110	96-106
RM-IMVENT-160-PVC LT GREY	145	5	Dark grey PVC	160	150-153
RM-IMVENT-75-PVC DK GREY	63	10		75	70-79
RM-IMVENT-110-PVC DK GREY	90			110	96-106
RM-IMVENT-160-PVC DK GREY	145	5	Plain	160	150-153
RM-IMVENT-75-PF	63	10		75	70-79
RM-IMVENT-110-PF	90			110	96-106

Spigot length: 250mm

Height above membrane (not including cowl): 300mm

Date generated: 13/02/2026

© FIXFAST Ltd 2026. All information is non-binding and without guarantee. Before using the products, all specifications and calculations must be checked by a suitably qualified person and local regulations must be observed. All rights reserved. Due to a policy of continuous development, FIXFAST reserves the right to change product specification and descriptions without notice. Subject to Fixfast's Terms & Conditions.