

RyMar® Cable Duct SB/PB



Application

These provide a weatherproof sleeve for cables or pipes which penetrate through a flat roof

The two elbows direct the cables and pipes either horizontally or vertically and helps prevent water ingress when installed correctly

Key Features

Can be supplied with two types of bends - PVC or stainless steel

Available with bitumen or single ply membrane flange or plain flange for liquid applied systems

Installation Details

Product Code	Base dia. (mm)	Duct dia. (mm)	Flange Material	Pipe Material	Duct height (mm)
RM-CD-75-PB-SBS	500 x 500	75	Bitumen	PVC	350
RM-CD-75-SB-SBS	500 x 500	75	Bitumen	Stainless Steel	350
RM-CD-75-PB-PVC-LT-GREY	330 x 330	75	PVC membrane	PVC	350
RM-CD-75-PB-PVC-DK-GREY	330 x 330	75	PVC membrane	PVC	350
RM-CD-75-SB-PVC-LT-GREY	330 x 330	75	PVC membrane	Stainless Steel	350
RM-CD-75-SB-PVC-DK-GREY	330 x 330	75	PVC membrane	Stainless Steel	350
RM-CD-75-PB-PF	350 x 350	75	Plain	PVC	350
RM-CD-110-PB-SBS	500 x 500	110	Bitumen	PVC	380
RM-CD-110-SB-SBS	500 x 500	110	Bitumen	Stainless Steel	380
RM-CD-110-PB-PVC-LT-GREY	330 x 330	110	PVC membrane	PVC	380
RM-CD-110-PB-PVC-DK-GREY	330 x 330	110	PVC membrane	PVC	380
RM-CD-110-SB-PVC-LT-GREY	330 x 330	110	PVC membrane	Stainless Steel	380
RM-CD-110-SB-PVC-DK-GREY	330 x 330	110	PVC membrane	Stainless Steel	380

Date generated: 13/02/2026

© FIXFAST Ltd 2026. All information is non-binding and without guarantee. Before using the products, all specifications and calculations must be checked by a suitably qualified person and local regulations must be observed. All rights reserved. Due to a policy of continuous development, FIXFAST reserves the right to change product specification and descriptions without notice. Subject to Fixfast's Terms & Conditions.