

Temperature and humidity transmitter LoRa / LoRaWAN

TX temperature and humidity with external probe






REMOTE T&H PROBE

RUGGED IP65 ENCLOSURE

EASY TO INSTALL

VERY LONG RANGE RADIO

REPLACEABLE BATTERY

VERY LONG BATTERY LIFE > 20 YEARS

SPECIFICATIONS

Enclosure and IP rating	ABS IP 65
Dimensions (l x w x h)	118 x 79 x 43 mm
Mounting	Wall / Collar / Din Rail (option)
Radio antenna	Embedded
Type of sensor	External temperature and humidity probe - cable lenght : 1.5 m
Sensor temperature range	- 40 / + 125 °C
Temperature sensor accuracy	+/- 0,5°C
Temperature sensor resolution	0,01°C
Sensor humidity range	0 to 100 % rH
TX working temperature	- 20 / + 55°C
Power supply	Replaceable 3.6 V D Lithium battery - Low battery alert
Radio frequency band	868 MHz bidirectional
Radio protocol	LoRa proprietary – LoRaWAN (mode change via jumper)
Output power	25mW (14 dBm)
Configuration	LoRa proprietary: configuration from the receiver's IP server LoRaWAN: setup via downlink
Battery autonomy	LoRa proprietary: 12 years with 5mn periodicity LoRaWAN: 15 years with 15mn periodicity (in SF9) Configurable periodicity
Encryption	LoRa proprietary: no encryption LoRaWAN: AES128
Addressing	LoRa proprietary: LoRa ID LoRaWAN: DEVEUI, APPEUI, APPKEY keys (OTAA)
LED	3 LED's
Approval	CE
Product reference	TX T&H EXT 600-034

DTM49-c