

# S28 Uninsulated Sliding System



## TECHNICAL PROPERTIES

Frame Depth	1.79 - 3.23 inch
Sash Depth	1.1 inch
Interlocking Depth	2.54 inch
Profile Wall Thickness	0.04 - 0.05 inch
Min. Glazing Thickness	0.16 inch
Max. Glazing Thickness	0.79 inch
Max. Sash Dimensions	47.24 x 86.61 inch
Max. Sash Weight	165.34 lbs

## PERFORMANCE VALUES

Min. Thermal Insulation	-
-------------------------	---

## APPLICATION OPTIONS

Sash Connection of 90°	-
Sash Connection of 45°	+
Sash With Glazing Bead	-
Sash Without Glazing Bead	+
Insect Screen Application	+

# S28 Uninsulated Sliding System



S28



S28 meets modern architectural trends and high performance requirements and it is an ideal solution for areas with temperate climate. It is an ideal sliding system for economical solutions for frames with and without sill.



GLASS GROUP LLC  
+1 (571) 269-2061  
info@glassgroup.us  
1 County Rd. Suite A12, Secaucus, NJ 07094

Trusted Solution Partner  
www.akpaas.com.tr



glassgroup.us



glassgroup.us

Sliding System



S28 Uninsulated Sliding System

