

S35 / S35T



TECHNICAL PROPERTIES

	S35 Uninsulated	S35T Insulated
Frame Depth	3.35 - 5.12 inch	3.78 - 6.2 inch
Sash Depth	1.38 inch	1.38 inch
Interlocking Depth	3.15 - 5.98 inch	3.35 - 6.18 inch
Profile Wall Thickness	0.05 - 0.06 inch	0.05 - 0.06 inch
Thermal Break	-	0.47 - 0.71 inch
Min. Glazing Thickness	0.79 inch	0.79 inch
Max. Glazing Thickness	0.87 inch	0.87 inch
Max. Sash Dimensions	62.99 x 110.24 inch	62.99 x 110.24 inch
Max. Sash Weight	352.74 lbs	352.74 lbs

PERFORMANCE VALUES

Min. Thermal Insulation	Uf: 3.33 W/(m².K)	Uf: 4.99 W/(m².K)
-------------------------	-------------------	-------------------

APPLICATION OPTIONS

Sash Connection of 90°	+	+
Sash Connection of 45°	-	-
Sash With Glazing Bead	-	-
Sash Without Glazing Bead	+	+
Insect Screen Application	+	+



GLASS GROUP LLC
+1 (571) 269-2061
info@glassgroup.us
1 County Rd. Suite A12, Secaucus, NJ 07094

Trusted Solution Partner
www.akpaas.com.tr



glassgroup.us

S35 / S35T Sliding System



It meets modern architectural trends and high performance requirements. With its multi-point locking mechanism, it offers safe and comfortable areas. Insulated and non-insulated, both systems with clamping lines provide a more transparent and minimal appearance.

S35



S35T



Sliding System

glassgroup.us

