

S38T



TECHNICAL PROPERTIES

Frame Depth	3.7 - 6.12 inch
Sash Depth	1.5 inch
Interlocking Depth	3.46 inch
Profile Wall Thickness	0.05 - 0.06 inch
Thermal Break	0.47 - 0.71 inch
Min. Glazing Thickness	0.24 inch
Max. Glazing Thickness	0.87 inch
Max. Sash Dimensions	62.99 x 110.24 inch
Max. Sash Weight	352.74 lbs

PERFORMANCE VALUES

Min. Thermal Insulation	Uf: 5.14 - 6.86 W/(m².K)
-------------------------	--------------------------

APPLICATION OPTIONS

Sash Connection of 90°	-
Sash Connection of 45°	+
Sash With Glazing Bead	+
Sash Without Glazing Bead	-
Insect Screen Application	+



GLASS GROUP LLC
+1 (571) 269-2061
info@glassgroup.us
1 County Rd. Suite A12, Secaucus, NJ 07094

Trusted Solution Partner
www.akpaas.com.tr



glassgroup.us

S38T Sliding System



S38T



S38T is an insulated sliding system with a modern and linear design line. It is ideal for renovation projects thanks to its ease of manufacture. It increases your security, maximizes insulation and tightness with a multi-point locking mechanism.



Sliding System

glassgroup.us

S38T Sliding System

