

Indoor Column Speaker

NT-(740A ICS+740B ICS+740C ICS+740D ICS)



Indoor Column Speaker (NT-740A ICS+740B ICS+740C ICS+740D ICS)

Nova NT-740 Indoor Column Speakers deliver professional audio in sleek, space-saving designs. The series includes four models (15W-40W) with 4"-6" drivers, offering 90dB sensitivity and 100-200Hz frequency response. Built in HIPS, MDF or aluminum (1.7-6kg), these 20V line-voltage speakers provide clear voice and background music for hotels, offices, and worship spaces. Choose from compact (275mm) to extended (650mm) models to match any architectural need while maintaining premium sound quality.

Key Features

Nova's NT-740 column speakers (15W-40W) pack 4"-6" drivers into sleek, space-saving designs (275-650mm). With 90dB sensitivity, 100-200Hz response, and durable HIPS/MDF/aluminum builds (1.7-6kg), they deliver clear audio for hotels, offices, and worship spaces. 20V line voltage ready.

TECHNICAL DATA SPECIFICATION

Model	NT-740A ICS	NT-740B ICS	NT-740C ICS	NT-740D ICS
Drive:	L: 6" / H:2"	L: 4" / H:2"	L: 4" / H:2"	L: 4" / H:2"
Rated Power:	15W	10W	20W	40W
Line voltage:	AC220V	AC220V	AC220V	AC220V
Sensitivity:	93dB	90dB	90dB	90dB
Frequency Response:	130-16KHz	130-15KHz	130-15KHz	100-20KHz
Dimension (mm):	200x105x275	160x110x300	160x110x430	145x125x650
Material:	HIPS	M.D.F	M.D.F	Aluminium
Weight (kg):	1.7	3.1	4.2	6.0

QUICK GUIDE

Nova's NT-740 column speakers (15W-40W) feature 4"-6" drivers in compact designs (275-650mm) with 90dB sensitivity. Ideal for background music and voice in hotels/offices, they offer 100-200Hz response in durable HIPS/MDF/aluminum enclosures (1.7-6kg).

