

Indoor Column Speaker

NT-(640A ICS+640B ICS+640C ICS+640D ICS)





Indoor Column Speaker (NT-640A ICS+640B ICS+640C ICS+640D ICS)

Nova NT-640 Indoor Column Speaker Series delivers professional distributed audio with four models (10W-40W) featuring 4" LF + 2" HF drivers. These 70V/100V compatible speakers offer 91-94dB sensitivity and 130-15KHz frequency response in space-saving MDF enclosures (300-690mm tall, 2.44-6.2kg), perfect for background music and paging in commercial spaces like hotels, retail stores, and offices. The graduated power options (10W-40W) and uniform frequency response ensure clear, balanced sound across all installation sizes.

Key Features

The Nova NT-640 series provides 10W-40W power through 4"+2" drivers (91-94dB sensitivity) in MDF column enclosures (2.44-6.2kg). With 70V/100V operation and 130-15KHz frequency response, these 300-690mm tall speakers offer scalable solutions for background music and voice in commercial installations.

TECHNICAL DATA SPECIFICATION

Model	NT-640A ICS	NT-640B ICS	NT-640C ICS	NT-640D ICS
Drive:	L: 4"/ H:2"	L: 4"/ H:2"	L: 4"/ H:2"	L: 4"/ H:2"
Rated Power:	10W	20W	30W	40W
Line voltage:	70V-100V	70V-100V	70V-100V	70V-100V
Sensitivity:	91dB	92dB	93dB	94dB
Frequency Response:	130-15KHz	130-15KHz	130-15KHz	130-15KHz
Dimension (mm):	160x110x300	160x110x430	160x110x560	160x110x690
Material:	M.D.F	M.D.F	M.D.F	M.D.F
Weight (kg):	2.44	3.42	4.66	6.2

QUICK GUIDE

Nova's NT-640 column speakers (10W-40W) feature 4"+2" drivers with 130-15KHz range and 91-94dB sensitivity. These 70V/100V-compatible MDF speakers (300-690mm tall) deliver clear audio for hotels, stores, and offices.

