

Professional Speaker

NT-(171 APS+171 BPS+171 CPS+171 DPS)



Professional Speaker (NT-171 APS+171 BPS+171 CPS+171 DPS)

NT-Series Professional Speakers deliver high-power sound with dual-driver full-range designs, featuring wide 90°×55° dispersion for superior coverage. Engineered with computer-optimized acoustics, these versatile speakers (350W-1000W compatible) excel in bars, live events, and as monitor/fill speakers. Their flexible installation options and subwoofer compatibility make them ideal for clubs, concerts, and mobile setups requiring robust, high-fidelity audio. Road-ready construction ensures durability for professional touring and fixed installations.

TECHNICAL DATA SPECIFICATION

Model	NT-171 APS	NT-171 BPS	NT-171 CPS	NT-171 DPS
System:	2-WAY FULL RANGE	2-WAY FULL RANGE	2-WAY FULL RANGE	2-WAY FULL RANGE
Frequency response:	60Hz-18KHz	55Hz-18KHz	55Hz-18KHz	40Hz-18KHz
Driver:	LF : 10" x 1 HF:1"x1	LF : 12" x 1 HF:1"x1	LF : 15" x 1 HF:1"x1	LF : 15" x 2 HF:1.5"x1
Nominal impedance:	8Ω	8Ω	8Ω	4Ω
Sensitivity:	95dB	97dB	97dB	98dB
Rated Power:	250W	300W	350W	700W
Maximum:	121dB	123dB	123dB	125dB
Size (mm):	350x320x530	395x380x565	470x440x685	560x500x1065
Package size (mm):	400x385x620	470x440x660	545x525x780	630x590x1180
Net weight (kg):	17	21.5	29	55.5
Gross weight (kg):	18.5	24.5	32.5	60

Key Features

The Nova NT-171 professional speaker series delivers premium 2-way full-range audio across four models: APS (250W, 10"+1"), BPS (300W, 12"+1"), CPS (350W, 15"+1"), and DPS (700W, dual 15"+1.5"). Offering wide frequency response (40Hz-18KHz), high sensitivity (95-98dB), and rugged construction (17-55.5kg), these speakers provide scalable solutions from portable setups to large venues, with the DPS model reaching 125dB SPL for maximum output. Ideal for live sound, DJs, theaters and outdoor events, the series combines professional-grade components with optimized cabinet designs for crystal-clear highs, powerful lows, and reliable performance in any professional audio environment.

