



Remote Paging Microphone (NT-340ES)

Remote Paging Microphone with 12-Zone Control expandable up to 120 zones using additional zone keypads. Designed for large-scale broadcasting and emergency announcements, this microphone system ensures clear, reliable communication across multiple areas. Operates on a stable DC 24V power supply for consistent performance in professional audio and PA systems.

TECHNICAL DATA SPECIFICATION

Model	NT-340ES
Power Consumption:	3W
Zone Capacity:	120 Zones
System Capacity:	32 Remote microphones
Line Inputs:	350mV, 10kΩ
Mic Input:	5mV, 600Ω
Frequency Response:	80Hz~16kHz
THD:	1% at RMS,1KHz
S/N Ratio:	>70dB
Operating Temp:	20°C to +70°C
Power Supply:	DC24V, ±20%
Humidity:	<95% no condensation
Dimension:	256(W)×149(H)×52(D) mm

KEY FEATURES

This remote paging microphone supports 12-zone control and can expand up to 120 zones using extra keypads. It is ideal for large buildings and emergency paging, delivering clear and stable voice communication. Operates on reliable DC 24V power for professional PA systems.

QUICK GUIDE

Connect the microphone to a DC 24V power source and link it to the PA system. Select the required zone using the keypad and press the talk button to make announcements. Add extra zone keypads to expand zone coverage when needed.

