

Touch-screen Type Microphone

NT-5500MST





Touch-screen Type Microphone (NT-5500MST)

Touch-screen Remote Paging Microphone with a 120-zone capacity, designed for large-scale PA and EVAC systems. Each system supports up to 32 remote microphones for flexible paging and control. Operates on a stable DC 24V power supply, ensuring reliable performance in critical communication environments.

TECHNICAL DATA SPECIFICATION

Model	NT-5500MST
Power Consumption:	3W
Zone Capacity:	120 Zones
System Capacity:	32 Remote microphones
Line Inputs:	350mV, 10kΩ
Mic Input:	5mV, 600Ω
Frequency Response:	80Hz~16kHz
THD:	1% at RMS,1KHz
S/N Ratio:	>70dB
Operating Temp:	-20°C to +70°C
Power Supply:	DC24V, ±20%
Humidity:	<95% no condensation
Dimension:	256(W)×149(H)×52(D) mm

KEY FEATURES

This touch-screen remote paging microphone supports up to 120 zones, making it ideal for large PA and EVAC systems. It allows connection of up to 32 remote microphones for flexible control and clear paging. Operates on a stable DC 24V power supply for reliable performance.

QUICK GUIDE

Connect the microphone to the DC 24V power supply and link it to the PA/EVAC system. Use the touch screen to select zones and make announcements. Multiple microphones can be added for expanded paging and system control.

