

Wall-Mount Speaker

NT-176A+176B+176C+176D WMP



Wall-Mount Speaker (NT-176A+176B+176C+176D WMP)

Wall-Mount Speakers are designed to deliver clear, balanced sound for commercial and public address applications. Equipped with high-quality full-range drivers, these speakers ensure excellent voice clarity and consistent audio performance across a wide frequency range of 90Hz–20kHz.

Supporting 70V–100V line systems, they are ideal for background music and paging in offices, schools, retail spaces, hospitals, hotels, and public facilities. The speakers offer multiple power tapping options (up to 80W depending on model), allowing flexible system design and easy integration with existing PA systems.

Constructed from durable HIPS material, the enclosures are lightweight, impact-resistant, and suitable for long-term indoor use. With a compact and modern wall-mount design, they blend seamlessly into any interior while providing reliable sound coverage. Available in multiple sizes and power ratings, the NT-176 WMP series delivers dependable performance, easy installation, and professional audio quality for a wide range of applications.

TECHNICAL DATA SPECIFICATION

Model	NT-176A WMP	NT-176B WMP	NT-176C WMP	NT-176D WMP
Drive:	L: 4"/ H: 1"	L: 5"/ H: 1"	L: 6"/ H: 1"	L: 8"/ H: 1"
Rated Power:	2.5W/5W/10W/20W/8Ω	3.75W/7.5W/15W/30W/8Ω	5W/10W/20W/40W/8Ω	7.5W/15W/30W/60W/8Ω
Line voltage/Impedence:	70V-100V	70V-100V	70V-100V	70V-100V
Sensitivity:	87dB	88dB	87dB	88dB
Frequency Response:	90-20KHz	90-20KHz	90-20KHz	90-20KHz
Dimension (mm):	220x150x135	255x178x155	310x213x195	417x289x255
Material:	HIPS	HIPS	HIPS	HIPS
Weight (kg):	2.5	3.1	3.7	6.6

KEY FEATURES

These wall-mount speakers deliver clear and balanced sound with wide frequency response, supporting 70V–100V PA systems for flexible installation. Built with durable HIPS material, they offer multiple power options, compact design, and reliable performance—ideal for offices, schools, retail spaces, and public address applications.

