

IP Network PA System

NT-905A+905B IP



IP Network PA System NT-905 IP

The NT-905A IP wall-mount network audio adapter features a built-in 10W Class-D amplifier with low-impedance speaker line and automatic 100V PA backup, enabling continuous audio transmission over IP/TCP networks. It supports remote program selection, volume and IP address control, local mic/line input with adjustable priority, and flexible installation anywhere on the LAN for cost-efficient, long-distance audio distribution.

PARAMETER		
Model	NT-905A IP	NT-905B IP
Network	Standard RJ45	Standard RJ45
Serial line	Db9	Db9
Power	AC 220V / 50Hz	AC 220V / 50Hz
Output sensitivity & source impedance	1000mV / 470 Ω 5.08	1000mV / 470 Ω 5.08
Input sensitivity & impedance	MIC: 10mV / 600 Ω 5.08 AUX: 400mV / 10k Ω 5.08	MIC: 10mV / 600 Ω 5.08 AUX: 400mV / 10k Ω 5.08
Power output	2 × 10W	2 × 10W
Standby power	1W	1W
Voice frequency	8Kbps–320Kbps	8Kbps–320Kbps
Frequency response	50Hz–15KHz	50Hz–15KHz
Sensitivity	≥70dB	≥70dB
Sampling rate	8K–48KHz	8K–48KHz
Frequency response	MP3	MP3
Harmonic distortion	≤1%	≤1%
Transfer speed	10Mbps	10Mbps
Support agreement	ARP, UDP, TCP/IP, ICMP, IGMP	ARP, UDP, TCP/IP, ICMP, IGMP
Network delay	≤50ms	≤50ms
Working Temperature	–20°C–60°C	–20°C–60°C
Dimension (mm)	250 × 180 × 70	231 × 120 × 40
Weight (kg)	3.0	0.85

