

RUSTICA

INSTALLATION INSTRUCTIONS

ENTRY BENCH + SHOE RACK



CONGRATULATIONS ON YOUR DECISION TO BRING HOME
AN AMERICAN MADE PRODUCT OF THE HIGHEST QUALITY

1-800-891-8312
support@rustica.com
www.Rustica.com




DESIGNED AND CRAFTED ENTIRELY IN THE
U.S.A.



DON'T BE A STRANGER
FOLLOW US ON SOCIAL MEDIA



Parts and Recommended Tools



PARTS

- A) End Pieces - Qty 4
- B) Shelves Qty 6
- C) Top Wood Bench - Qty 6 Tongue & Groove Slats
- D) Cross Supports - Qty 4
- E) Angle Brackets - Qty 8
- F) Rubber Feet - Qty 8
- G) Philips Bolts and Lock Bolts - Qty 44
- H) Philips Screws - Qty 12

- 1) Assemble one of the shelves and two of the sides as shown. Loosely install the bolts and lock nuts in the indicated corners (Figure 1).
- 2) Assemble a second shelf and the two diagonal braces as shown. Leave the opposite ends of the braces free for now. Loosely install bolts and nuts where indicated (Figure 2).
- 3) Install the third shelf and attach the other ends of the diagonal braces (Figure 3).
- 4) Assemble the slats. Line up the ends and use the included black wood screws to attach two angle brackets to the face of the slats, positioned as shown below. Each bracket has a side with three holes and a side with two holes. Take care to attach the side with THREE holes to the slats (Figure 4).
- 5) Install the assembled top so the brackets on the slats go in between the already assembled sides. Use four more bolts and nuts in the indicated locations (Figure 5)
- 6) Install the remaining two brackets at the bottom of the sides. Apply the stick-on rubber pads if desired (Figure 6).
- 7) To connect the two sides together, bolt the sides together at the four indicated locations. This may be easiest to do before tightening the fasteners in the rest of the unit (Figure 7).
- 8) Tighten all the loose fasteners, and you're finished!



