

Certified by ISO9001 International Quality Control System

JXM Series LED Blank-out Signs & Lane Control Signs

Features & Specifications

- Compliance with applicable ITE/MUTCD specifications
- Low power consumption & long operating lifetime LEDs (100,000 hours)
- Aluminum housing and door frame with 0.125 inch thickness
- Minimum of 30 degree viewing angel centered optical axis
- Fully compatible with NEMA controllers/conflict monitors
- Moisture proof and mechanical vibration protection
- Complete blank out when de-energized
- Stainless steel fasteners and hardware



Model Number	JXM-BLK	JXM-LC
Size (in)	MUTCD Specified Sizes	MUTCD Specified Sizes
Symbol/Words	MUTCD Specified	MUTCD Specified
LED Color	As Needed	Red/Yellow/Green/White
Voltage (Typical)	120V - 60hz	120V - 60hz
Voltage Range	80V - 135V	80V - 135V
Power (W) Typical	60 ~ 120	30 ~ 50
Operation Temperature	-40°F to +165°F	-40°F to +165°F
Power Factor	> 0.9	> 0.9

All characteristics, including visual characters, chromaticity, moisture and vibration resistance, electronic noise, transient protection, etc., are conformed to standards specified in ITE LED Signal Modules.

For additional technical information or sales support regarding these and other LED products, please contact us at (972) 480-0888 or visit our website at www.trastarusa.com.

