van besouw

2609

About

Type of manufacture	Tufted	ISO 2424
Width	400 and 500 cm	ISO 3018
Type of surface	Cut pile	ISO 2424
Pile material	100% PA 6.6	ISO 2424
Backing	Actionback	ISO 2424
Pile weight	1675 g/m^2	ISO 2424
Total weight	2575 g/m^2	ISO 8543
Pile height	10,0 mm	ISO 1766
Total height	11,0 mm	ISO 1765

Application

Use classification	23 residential use / 32 commercial use		EN 1307 / ISO 10361
Suitability for use on stairs	Suitable for residential and commercial use		EN 1307 / ISO 12951
Suitability for castor chair	Suitable for residential and commercial use		EN 1307 / ISO 4918
Antistatic behaviour	≤ 2.0 kV at 25%RH		ISO 6356
Thermal resistance	0.20 m^2 K/W		EN 12667
Burning behaviour	B_{fl}-s1		EN 13501-1 / ISO 9239-1
Colourfastness to light	≥ 5		EN 1307 / ISO 105-B02
Impact sound insulation	Δ L_w 31 dB		EN 717-2 / ISO 10140-3
Comfortclass	LC5		EN 1307 / EN 8543
Slip resistance	DS		EN 14041 / EN 13893

creative colour concept: available in custom colours from 400 m^2.

Address Sasdijk 14, 8281 BM Genemuiden (NL) Phone +31 (0) 38 385 8818 E-mail info@besouw.nl Site www.besouw.nl