

## PRODUCT DATA SHEET

# EVERBUILD® Ultra Hard Floor Varnish

CLEAR QUICK DRYING FLOOR VARNISH FOR A 'HAMMER HARD' TOUGH FINISH

### PRODUCT DESCRIPTION

EVERBUILD® Ultra Hard Floor Varnish is a clear quick drying varnish ideal for use on most common types of wooden floors including hardwood, softwood, hard-board, chipboard and composite wooden boards. EVERBUILD® Ultra Hard Floor Varnish has been specifically developed to provide an ultra-hard scratch resistant natural finish to most interior wooden floors. EVERBUILD® Ultra Hard Floor Varnish provides superior protection for wooden floors and has a hammer hard, tough finish to protect wood against scratches and spills. EVERBUILD® Ultra Hard Floor Varnish is touch dry in 30 mins.

### USES

Suitable for use in kitchens, bathrooms, lounge, dining areas or where heavy foot traffic would be expected.

### CHARACTERISTICS / ADVANTAGES

- Superior protection for wooden floors.
- Low solvent formula
- Touch dry in 30 minutes.
- Enhances and protects wood against scratches and spills.
- Clear finish, no discoloration.
- Withstands heavy foot traffic.

### PRODUCT INFORMATION

|                            |   |
|----------------------------|---|
| <b>Packaging</b>           | 750ml & 2.5ltr tins   |
| <b>Appearance / Colour</b> | White liquid, dries clear   |
| <b>Shelf Life</b>          | 2 years from date of manufacture when stored as directed.   |
| <b>Storage Conditions</b>  | Store in cool dry conditions between + 5 and +25°C. Storage outside these conditions will dramatically reduce shelf life. PROTECT FROM FROST. |
| <b>Density</b>             | ~1.0 g/cm <sup>3</sup>  |
| <b>Viscosity</b>           | Dynamic viscosity 500-1000cPs @ 20°C  |

### APPLICATION INFORMATION

|                    |   |
|--------------------|---|
| <b>Consumption</b> | Up to 16 square metres per litre. Coverage will vary depending on the absorbency of the wood.   |
| <b>Curing Time</b> | Can be walked on after approximately 8 hours depending on ambient temperature and conditions. Allow 72 hours before subjecting to heavy foot traffic. Do not cover with carpets or rugs for at least 7 days. Protect from water for 5 days. |

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

On unvarnished floors ensure wood is clean, dry and free from dirt or dust by wiping with a soft cloth and white spirit. Any existing coatings must be removed prior to application with a suitable sander using 120 grade abrasive paper. A suitable dust mask should be worn while sanding. Allow any dust to settle then vacuum the floor to remove any dust or debris. Fill in any holes or surface imperfections using Everbuild Multi-Purpose Wood Filler.

Existing varnished floors should be thoroughly sanded using 120 grade abrasive paper to provide a key for EVERBUILD® Ultra Hard Floor Varnish to be applied. Floors should be vacuumed, wiped down with white spirit and allowed to dry. Any existing varnish in poor condition should be completely removed prior to application.

### APPLICATION

Stir product well before use and periodically during application. Brush apply EVERBUILD® Ultra Hard Floor Varnish following the direction of the wood grain. Apply a minimum of 3 coats allowing 1 hour between coats. Lightly sand the surface before applying the final coat. Always apply the varnish to a wet edge working systematically across the surface keeping the wet edge together as much as possible to avoid overlap.

### CLEANING OF TOOLS

Clean brushes thoroughly after use with warm soapy water.

### LIMITATIONS

- Do not use externally.
- Always test a small inconspicuous area prior to full application.
- Do not use below 10°C.
- Do not use in areas subject to prolonged water contact.
- Do not use on laminate floors.
- It is the user's responsibility to determine suitability for use. If in doubt contact Technical Services for advice.

### VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

See MSDS for full list of hazards.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**EVERBUILD BUILDING PRODUCTS LTD**

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

**SIKA LIMITED**

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited

**SIKA IRELAND LIMITED**

Ballymun Industrial Estate  
Ballymun  
Dublin 11, Ireland  
Tel: +353 1 862 0709  
Web: [www.sika.ie](http://www.sika.ie)  
Twitter: @SikaIreland

EVERBUILDUltraHardFloorVarnish-en-GBEVER-(03-2018)-1-1.pdf

Product Data Sheet  
EVERBUILD® Ultra Hard Floor Varnish  
March 2018, Version 01.01  
020813020010000013