

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

Version 1.2

1.1 Product identifier	
Trade name 1.2 Relevant identified uses	Stick2 Rapid Epoxy Syringe/Tube Resin (A) for the substance or mixture and uses advised against
Product use	: Adhesive
1.3 Details of the supplier of	the safety data sheet
Company	<ul> <li>Everbuild – A Sika Company Site 41</li> <li>Knowsthorpe Way</li> <li>Cross Green Industrial Estate</li> <li>Leeds</li> <li>West Yorkshire LS9 0SW</li> <li>United Kingdom</li> </ul>
Telephone	: 0113 240 3456
E-mail address	: everbuild.sds@uk.sika.com

#### 1.4 Emergency telephone number

Emergency telephone num-	:	0044 113 240 3456 (office hours only)
ber		

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	72/2008)
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Stick2 Rapid Epoxy Syringe/Tube Resin (A) Revision Date 21.06.2019



Circuit a la succession			
Signal word	•	Warning	
Hazard statements	:	H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	P101	If medical advice is needed, have product container or label at hand.
		P102	Keep out of reach of children.
		Prevention:	
		P261	Avoid breathing dust/ fume/ gas/ mist/ va- pours/ spray.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ eye protection/ face protection.
		Disposal:	
		P501	Dispose of contents/container in accordance with local regulation.

Version 1.2

Hazardous components which must be listed on the label:

 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

### Additional Labelling

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
reaction product: bisphenol-A-	25068-38-6	Eye Irrit. 2; H319	>=80
(epichlorhydrin); epoxy resin	500-033-5	Skin Irrit. 2; H315	
(number average molecular	01-2119456619-26-	Skin Sens. 1; H317	
weight $\leq$ 700)	XXXX	Aquatic Chronic 2;	
		H411	



### **SECTION 4: First aid measures**

4.1 Description of first aid measures			
General advice :	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.		
If inhaled :	Move to fresh air. Consult a physician after significant exposure.		
In case of skin contact :	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.		
In case of eye contact :	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.		
If swallowed :	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.		
4.2 Most important symptoms and effects, both acute and delayed			
Symptoms :	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.		
Risks :	irritant effects sensitising effects		
	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.		
4.3 Indication of any immediate medical attention and special treatment needed			
Treatment	Treat symptomatically		

Version 1.2

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

<b>5.1 Extinguishing media</b> Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local ci cumstances and the surrounding environment.	r-
5.2 Special hazards arising from a Specific hazards during fire-		e substance or mixture Do not allow run-off from fire fighting to enter drains or wate	er
Country GB 100000012919			3 / 13

### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Stick2 Rapid Epoxy Syringe/Tube Resin (A) Revision Date 21.06.2019



	fighting Hazardous combustion prod- ucts	:	courses. No hazardous combustion products are known
5.3	Advice for firefighters Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Version 1.2

### **SECTION 6: Accidental release measures**

• •	<ul> <li>ve equipment and emergency procedures</li> <li>Use personal protective equipment. Deny access to unprotected persons.</li> </ul>
<b>6.2 Environmental precautions</b> Environmental precautions	<ul> <li>Do not flush into surface water or sanitary sewer system.</li> <li>If the product contaminates rivers and lakes or drains inform respective authorities.</li> </ul>
6.3 Methods and material for conta Methods for cleaning up	ainment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

7.1 Precautions for safe handlin	g	
Advice on safe handling	<ul> <li>Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area.</li> </ul>	

### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Stick2 Rapid Epoxy Syringe/Tube Resin (A)

Revision Date 21.06.2019



		Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage,	inc	luding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

Version 1.2


### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

<b>Personal protective equipment</b> Eye protection :	
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (0,4 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	No special measures required.



Version 1.2




#### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties Appearance liquid : Colour yellow Odour irritating Odour Threshold No data available No data available pН • Melting point/range / Freezing : No data available point Boiling point/boiling range No data available > 150 °C Flash point Method: closed cup Evaporation rate No data available Flammability (solid, gas) No data available • Upper explosion limit / Upper No data available : flammability limit Lower explosion limit / Lower No data available · flammability limit Vapour pressure 0.01 hPa · Relative vapour density No data available Density ca. 1,16 g/cm3 (20 °C) • Solubility(ies) Water solubility insoluble Solubility in other solvents : No data available Partition coefficient: n-: No data available octanol/water Auto-ignition temperature : No data available Decomposition temperature No data available : Country GB 100000012919





Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: < 20,5 mm2/s (40 °C)
Explosive properties	: No data available
Oxidizing properties	: No data available

#### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

Version 1.2

#### 10.4 Conditions to avoid

Conditions to avoid	:	No data available
---------------------	---	-------------------

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

#### Acute toxicity

Not classified based on available information.

#### Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecula weight ≤ 700):		
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg

Revision Date 21.06.2019

Version 1.2



#### Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity Not classified based on available information.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

### **Components:**

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700): Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Toxicity to daphnia and other	•	EC50 (Daphnia magna (Water flea)): 1,8 mg/l
Toxioley to adplittle and other	•	
aguatic invertebrates		Exposure time: 48 h

Exposure time: 96 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Country GB 10000012919



Assessment	: This substance/mixture contains no co to be either persistent, bioaccumulative very persistent and very bioaccumulati 0.1% or higher	e and toxic (PBT), or
12.6 Other adverse effects		
Product:		
Additional ecological infor- mation	: An environmental hazard cannot be ex unprofessional handling or disposal.	cluded in the event of

Version 1.2

Toxic to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	20 01 27* paint, inks, adhesives and resins containing dan- gerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

## **SECTION 14: Transport information**

14.1 UN number			
ADR	:	UN 3082	
IMDG	:	UN 3082	
ΙΑΤΑ	:	UN 3082	
14.2 UN proper shipping name			
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIE N.O.S. ((reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight > 1100))	,
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIE	D,
Country GB 100000012919			9 / 13



ΙΑΤΑ	:	N.O.S. (reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight > 1100)) Environmentally hazardous substance, liquid, n.o.s. ((reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight > 1100))
14.3 Transport hazard class(es)		
ADR	:	9
IMDG	:	9
ΙΑΤΑ	:	9
14.4 Packing group		
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code IMDG		III M6 90 9 (-)
Packing group Labels EmS Code	:	III 9 F-A, S-F
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous Dangerous Goods
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	· · ·	964 Y964 III Miscellaneous Dangerous Goods
14.5 Environmental hazards		
<b>ADR</b> Environmentally hazardous	:	no
IMDG Marine pollutant	:	no
IATA (Passenger) Environmentally hazardous	:	no
IATA (Cargo) Environmentally hazardous	:	no
14.6 Special precautions for user	•	
The transport classification(s)	nrc	wided berein are for informational purposes only, and solely based

Version 1.2

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.



Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Version 1.2

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

15.1	15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture					
	International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors					
	REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).		
	REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable		
	Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de-	:	Not applicable		
	Regulation (EC) No 850/2004 on lutants	persistent organic pol-	:	Not applicable		
	REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)			Not applicable		
	REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	strea l/or gula	am suppliers, and/or tion, and/or		
	Seveso III: Directive 2012/18/EU jor-accident hazards involving da E2			t and of the Council on the control of ma- RDS		
	Volatile organic compounds :	Law on the incentive ta (VOCV) no VOC duties	ax fo	or volatile organic compounds		
				4 November 2010 on industrial ution prevention and control)		
	If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.					
	Health, safety and environ- mental regulation/legislation specific for the substance or	Health and Safety at V	Vork	Act 1990 & Subsidiary Regulations Act 1974 & Subsidiary Regulations zardous to Health Regulations		



mixture:

(COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Version 1.2

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

Full text of H-Statements		
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H411	÷	Toxic to aquatic life with long lasting effects.
Full text of other abbreviat	ions	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Skin Irrit. Skin Sens.	-	Skin irritation Skin sensitisation
ADR	:	European Agreement concerning the International Carriage of
	·	Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of test animals)
LC50		Median lethal concentration (concentrations of the chemical in
2000	•	air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT PNEC	:	Persistent, bioaccumulative and toxic
REACH	:	Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament
REACH	•	and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
Further information		
Classification of the mixtu	-	Classification procedure:
Skin Irrit. 2	H3	Calculation method
Eye Irrit. 2	H3	Calculation method
Skin Sens. 1	H3	Calculation method

Country GB 10000012919

### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Stick2 Rapid Epoxy Syringe/Tube Resin (A) Revision Date 21.06.2019



Aquatic Chronic 2

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Version 1.2

Changes as compared to previous version !

H411

GB / EN