

# Tecnic Hybriflex 40

## DECLARATION OF PERFORMANCE

### No. 15299220

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	HYB40
2	<b>INTENDED USE/S</b>	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements
3	<b>MANUFACTURER:</b>	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate Leeds, LS9 0SW
4	<b>AUTHORISED REPRESENTATIVE:</b>	N/A
5	<b>SYSTEM/S OF AVCP:</b>	3
6a	<b>HARMONISED STANDARD:</b>	EN 15651-1
	Notified body/ies:	1213

#### Declaration of Performance

HYB40  
15299220  
2021/05 , ver. 03  
1213

---

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	NPD		
Loss of volume	≤ 10 %		
Resistance to flow	≤ 3 mm		
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60 %		
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 60%		EN 15651-1 : 2012
Durability	Pass		

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas  
Function: Technical Product  
Coordinator  
At Leeds on 26 May 2021

Name : Emma Taylor  
Function: Product Manager  
At Leeds on 26 May 2021



---

End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

HYB40  
15299220  
2021/05 , ver. 03  
1213



14

Everbuild

DoP No. 15299220

EN 15651-1 : 2012

Notified Body 1213

Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements

Reaction to fire	NPD
Loss of volume	≤ 10 %
Resistance to flow	≤ 3 mm
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60 %
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 60%
Durability	Pass

<http://www.everbuild.co.uk/downloads/>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

HYB40  
15299220  
2021/05 , ver. 03  
1213

**Declaration of Performance**

HYB40  
15299220  
2021/05 , ver. 03  
1213

