

Everbuild Tecnic[®] Silicone 996 Colours

DECLARATION OF PERFORMANCE No. 93114518

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	996COL
2	INTENDED USE/S	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 2: Sealants for Glazing
3	MANUFACTURER:	Everbuild – A Sika Company Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW UK
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	3
6a	HARMONISED STANDARD:	EN15651-2:2012
	Notified body/ies:	0074

Declaration of Performance

996COL
93114518
2021/08 , ver. 02
1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to Fire	NPD		
Loss of volume	≤ 10 %		
Vertical flow resistance	≤ 3 mm		
Adhesion/cohesion properties after exposure to heat water and artificial light	NF		
Elastic recovery	≥ 60 % at 60 % elongation		
Tensile properties (i.e. secant modulus): - for non-structural low modulus sealants used in joints in cold climate areas (-30 °C)	≤ 0.9 MPa		EN15651-2: 2012
Tensile properties (i.e. at maintained extension): - for non-structural sealants used in joints in cold climate areas (-30 °C)	NF		
Durability	Pass		
Release of chemicals dangerous to the environment and health	See SDS		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 04 August 2021

Name : Emma Taylor
Function: Product Manager
At Leeds on 04 August 2021



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

996COL
93114518
2021/08 , ver. 02
1213



14

Everbuild – Sika Company, Leeds, UK

DoP No. 93114518

EN15651-2:2012

Notified Body 0074

Sealant for non-structural use in joints in buildings and pedestrian walkways Part 2: Sealants for Glazing

Reaction to Fire	NPD
Loss of volume	≤ 10 %
Vertical flow resistance	≤ 3 mm
Adhesion/cohesion properties after exposure to heat water and artificial light	NF
Elastic recovery	≥ 60 % at 60 % elongation
Tensile properties (i.e. secant modulus): - for non-structural low modulus sealants used in joints in cold climate areas (-30 °C)	≤ 0.9 MPa
Tensile properties (i.e. at maintained extension): - for non-structural sealants used in joints in cold climate areas (-30 °C)	NF
Durability	Pass
Release of chemicals dangerous to the environment and health	See SDS

<http://www.everbuild.co.uk/downloads/>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

996COL

93114518

2021/08 , ver. 02

1213

Declaration of Performance

996COL
93114518
2021/08 , ver. 02
1213

