



# SIKAFLOOR 440 LEVEL

# DECLARATION OF PERFORMANCE

# No. 49903730

1	UNIQUE IDENTIFICATION		
	CODE OF THE PRODUCT-		
	TYPE:		

SKLEV440FB20

2 INTENDED USE/S

Cementitious screed material for use internally and externally

3 MANUFACTURER:

Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Ind. Estate

Leeds, LS9 0SW

4 AUTHORISED REPRESENTATIVE:

N/A

5 SYSTEM/S OF AVCP:

System 4

6a HARMONISED STANDARD:

EN 13813:2002

Notified body/ies:

N/A

### 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class F		
Release of corrosive substances	CT		
Water permeability	NPD		
Water Vapour permeability	NPD	***************************************	
Compressive Strength	C25	The second secon	
Flexural Strength	F5		EN 12012
Abrasion / Wear Resistance	AR0.5		EN 13813
Sound insulation	NPD		
Sound absorption	NPD		
Thermal resistance	NPD		
Chemical resistance	NPD		

### 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Paul Thomas

Function: Technical Product

Coordinator

At Leeds on 06 August 2019

Name: Andrew Stockill

Function: QA / QC Supervisor

At Leeds on 06 August 2019

End of information as required by Regulation (EU) No 305/2011





#### Everbuild Building Products LTD, Leeds, UK

DoP No. 49903730

EN 13813:2002

Notified Body N/A

### Cementitious screed material for use internally and externally

Reaction to fire	Class F	
Release of corrosive substances	СТ	F THE STATE OF THE
Water permeability	NPD	2 L 4 L
Water Vapour permeability	NPD	4 22.
Compressive Strength	C25	pro a - a - a - a - a - a - a - a - a -
Flexural Strength	F5	- 1 O O
Abrasion / Wear Resistance	AR0.5	- 1* - 1
Sound insulation	NPD	4 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Sound absorption	NPD	1 m
Thermal resistance	NPD	- XI
Chemical resistance	NPD	

http://dop.sika.com

## **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

### **LEGAL NOTE**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance SKLEV440FB20 49903730 Aug 2019 , ver 01. 1213 Template for translation. Only for internal use



