

SikaFlex EBT+ Colours

DECLARATION OF PERFORMANCE No. SKEBTCOL/1-CPR/2013

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	SKFLEXEBT
2	INTENDED USE/S	Sealant for exterior and interior applications, facade
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate, LS9 0SW Leeds
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 15651-1:2012
	Notified body/ies:	1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Resistance to flow	≤3 mm	System 3	
Loss of volume	≤10 %	System 3	
Tensile properties (i.e. elongation): at maintained extension after water immersion (elastic)	NF at 100%	System 3	EN 15651-1:2012
Tensile properties (i.e. at maintained extension): for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 100%	System 3	
Durability	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product Co-ordinator
At Leeds on 20 March 2018



Name : Andrew Stockill
Function: QA/QC Supervisor
At Leeds on 20 March 2018



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikaflex EBT+ Colours
SKEBTCOL/1-CPR/2013
2018.03 , ver. 01
1213



Everbuild Building Products LTD, Leeds, UK

DoP No. SKEBTCOL/1-CPR/2013

EN 15651-1:2012

Notified Body 1213

Sealant for exterior and interior applications, facade

Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	NPD
Resistance to flow	≤3 mm
Loss of volume	≤10 %
Tensile properties (i.e. elongation): at maintained extension after water immersion (elastic)	NF at 100%
Tensile properties (i.e. at maintained extension): for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 100%
Durability	Pass

<http://www.everbuild.co.uk>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikaflex EBT+ Colours
SKEBTCOL/1-CPR/2013
2018.03 , ver. 01
1213



Declaration of Performance
Sikaflex EBT+ Colours
SKEBTCOL/1-CPR/2013
2018.03 , ver. 01
1213

