

SIKACEM[®]-125 ACCELERATOR

DECLARATION OF PERFORMANCE No. 45277231

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	SKACC
2	INTENDED USE/S	Hardening and accelerating admixture
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate, LS9 0SW
4	AUTHORISED REPRESENTATIVE:	Not Applicable
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN934-2:2009 +A1:2012
	Notified body/ies:	0120

Declaration of Performance

SKACC

45277231

2021/06, ver. 01

1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Chloride ion content	<0.1% w/w		
Alkali Content	<2% w/w		
Corrosion Behavior	Contains the following components from En934-1:2008 Annex A.2; Calcium Nitrate		
Compressive Strength	>120% of control 20°C and 24 hours		
	>90% of control 20°C and 28 days		EN934-2:2009
	>130% of control 5°C and 48 hours		
Air Content in Fresh Concrete	≤2% by volume above control		
Dangerous Substances	None (see MSDS)		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product Co-ordinator
At Leeds on 25 June 2021

Name : Mariam Maqsood
Function: Product Manager
At Leeds on 25 June 2021



.....



End of information as required by Regulation

Declaration of Performance

SKACC
45277231
2021/06 , ver. 01
1213



21

Everbuild Building Products LTD, Leeds, UK

DoP No. 45277231

EN934-2:2009 +A1:2012

Notified Body 0120

Hardening and accelerating admixture

Chloride ion content	<0.1% w/w
Alkali Content	<2% w/w
Corrosion Behavior	Contains the following components from En934-1:2008 Annex A.2; Calcium Nitrate
Compressive Strength	>120% of control 20°C and 24 hours >90% of control 20°C and 28 days >130% of control 5°C and 48 hours
Air Content in Fresh Concrete	≤2% by volume above control
Dangerous Substances	None (see MSDS)

For DoC see www.everbuild.co.uk/downloads/**ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SKACC
45277231
2021/06 , ver. 01
1213



Declaration of Performance

SKACC
45277231
2021/06 , ver. 01
1213

