

# Sikaflex® EBT+ Clear

## DECLARATION OF PERFORMANCE

## No. 58871980

1	UNIQUE IDENTIFICATION
	CODE OF THE PRODUCT-
	TYPE:

### **SKFLEXEBTCR**

2 INTENDED USE/S

Sealants for non-structural use in joints in buildings and

pedestrian walkways

Part 1: Sealants for façade; Sealants for exterior and

interior applications

Part 3: Sealants for sanitary joints; Sealing of joints applied in sanitary areas in the interior of buildings exposed to

non-pressurised water

3 MANUFACTURER: EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way, Cross Green Industrial Estate,

Leeds, LS9 OSW, UK

4 AUTHORISED Not applicable

5 SYSTEM/S OF AVCP: System 3

**6a HARMONISED STANDARD:** EN 15651-1:2012 and EN15651-3:2012

Notified body/ies: 2538

SKFLEXEBTCR 58871980 2021/05 , ver. 01 1213

## 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Release of dangerous chemicals	See SDS		
Reaction to fire	NPD		
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10%		
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%		
Tensile properties (ISO8339) for non-structural low modulus sealant used in cold climate	≤0.9 MPa		EN 15651- 1:2012
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 60%		
Durability	Pass		
Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Essential Characteristics	Performance	·	
Release of dangerous chemicals	See SDS	·	
Reaction to fire	NPD		
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20%		EN 15651-
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%		3:2012
Microbiological Growth	2		
Durability	Pass		

## 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Paul Thomas Function: Technical Product

Coordinator

At Leeds on 04 June 2021

Name: Emma Taylor

Function: Product Manager At Leeds on 07 June 2021

End of information as required by UKCA Regulation



Everbuild Building Products LTD, Leeds, UK

DoP No. 58871980


EN 15651-1:2012

Notified Body 2538

Sealants for non-structural use in the joints in buildings and pedestrian walkways for Sealants for exterior and interior applications

Release of dangerous chemicals	See SDS
Reaction to fire	NPD
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%
Tensile properties (ISO8339) for non-structural low modulus sealant used in cold climate	≤0.9 MPa
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 60%
Durability	Pass

for DoP see www.everbuild.co.uk/downloads/





21

#### Everbuild Building Products LTD, Leeds, UK

DoP No. 58871980

EN 15651-3:2012

Notified Body 2538

Sealants for non-structural use in the joints in buildings and pedestrian walkways for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurized water

Release of dangerous chemicals	See SDS
Reaction to fire	NPD
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20%
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%
Microbiological Growth	2
Durability	Pass

for DoP see www.everbuild.co.uk/downloads/

### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

### **LEGAL NOTE**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

