

EVERBUILD® JETCEM RAPID REPAIR CEMENT

DECLARATION OF PERFORMANCE No. 44690065

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	JETCEM
2	INTENDED USE/S	Concrete repair product for non- structural repair. CC Mortar (based on hydraulic cement)
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate LS9 0SW, Leeds
4	AUTHORISED REPRESENTATIVE:	Not Applicable
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN1504-3:2005
	Notified body/ies:	0120

Declaration of Performance

JETCEM
44690065
2021/06 , ver. 01
1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compressive Strength	Class R4		EN1504-3:2005
Chloride Ion Content	≤0.05%		
Adhesion Strength by pull off	≥1.5MPa		
Restrained Shrinkage/Expansion	NPD		
Carbonation Resistance	NPD		
Elastic Modulus	≥15Gpa		
Thermal Compatibility: Part 4 Dry Cycling	≥0.8MPa		
Skid Resistance	NPD		
Coefficient of Thermal Expansion	NPD		
Capillary Adsorption	≤0.5kg/m ² h ^{0.5}		
Dangerous Substances	Complies with 5.4		
Reaction to Fire	Class A1		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 15 June 2021

Name : Mariam Maqsood
Function: Product Manager
At Leeds on 15 June 2021



End of information as required by Regulation

Declaration of Performance

JETCEM
44690065
2021/06 , ver. 01
1213



21

Everbuild Building Products LTD, Leeds, UK

DoP No. 44690065

EN1504-3:2005

Notified Body 0120

Concrete repair product for non- structural repair. CC Mortar (based on hydraulic cement)

Compressive Strength	Class R4
Chloride Ion Content	≤0.05%
Adhesion Strength by pull off	≥1.5MPa
Restrained Shrinkage/Expansion	NPD
Carbonation Resistance	NPD
Elastic Modulus	≥15Gpa
Thermal Compatibility: Part 4 Dry Cycling	≥0.8MPa
Skid Resistance	NPD
Coefficient of Thermal Expansion	NPD
Capillary Adsorption	≤0.5kg/m ² h ^{0.5}
Dangerous Substances	Complies with 5.4
Reaction to Fire	Class A1

www.everbuild.co.uk/downloads/

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

JETCEM
44690065
2021/06 , ver. 01
1213

Declaration of Performance

JETCEM

44690065

2021/06 , ver. 01

1213

4/4

BUILDING TRUST

