

PRODUCT DATA SHEET

EVERBUILD® MAMMOTH® BUILDERS PVC TAPE

Strong PVC builders tape

PRODUCT DESCRIPTION

EVERBUILD® MAMMOTH® BUILDERS PVC TAPE is a strong, versatile, all-weather adhesive that is ideal for jointing all PVC and polythene sheets and membranes. This product can be used in cold weather applications, down to 0 °C. It provides good resistance to abrasion, moisture, alkalies, acids, corrosion and resistance to varying weather conditions. EVERBUILD® MAMMOTH® BUILDERS PVC TAPE is perfect for contamination barrier fastening, dust sealing of sheets and many other uses in construction and industry.

USES

- Contamination barrier fastening.
- Dust sealing of sheets.
- For heavy duty sealing, repairing and waterproofing.
- Suitable for insulating air ducts and underground pipes.

CHARACTERISTICS / ADVANTAGES

- Will stick to most common surfaces, including polythene and PVC.
- Good resistance to abrasion, moisture, alkalies, acids, corrosion and varying weather conditions.
- Removes easily no adhesive residue.
- Can be used in extensive temperature, moisture and humid conditions.
- Flame retardent.

Adhesion to Steel	3.5 N/25 mm
Adhesion to Backing	3.5 N/25 mm
Dielectric Strength	5 kV/Min

APPROVALS / STANDARDS

EN 60454 type 2 for electrical use

PRODUCT INFORMATION

Packaging	50 mm x 33 m & 75 mm x 33 m rolls
Shelf Life	14 months from date of manufacture.
Storage Conditions	Store in cool dry conditions between +10 °C and +27 °C. Safe in normal use however as a precaution keep polythene outer packaging away from children.
Appearance / Colour	Black
Thickness	0.15 mm
Elongation at Break	150 % @ 23 °C

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Product Data Sheet

EVERBUILD® MAMMOTH® BUILDERS PVC TAPE July 2024, Version 02.03 020514080000000031

LIMITATIONS

- Do not use on surfaces that bleed oils or plasticiser.
- It is the user's responsibility to determine suitability for use. If in doubt contact Technical Services for ad-

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Ensure surfaces to which tape is to be applied are clean sound and dry.

APPLICATION METHOD / TOOLS

Remove outer packaging from roll of tape. Peel required amount of tape from roll pressing firmly into place while unrolling. Cut with a knife when finished.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.







Product Data Sheet

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited

EVERBUILDMAMMOTHBUILDERSPVCTAPE-en-GBEVER-(07-2024)-2-3.pdf





