

INDICE: **Valvole di massima pressione**
 INDEX: Maximum pressure valves

CATEGORIA: **Max 56 MPa**
 CATEGORY:

ARTICOLO:
 PRODUCT NAME:

SVL50

PRESSIONE AMMISSIBILE/PERMISSIBLE PRESSURE 560 bar 56 MPa 8100 psi
PORTATA NOMINALE/RATED FLOW 100 l/min 26,4 USGpm
TEMPERATURA NOMINALE/RATED TEMPERATURE 90 °C 194 °F

CODICE CODE	ENTRATA INLET	BY-PASS	INTERVALLO DI TARATURA ALLOWABLE SETTING PRESSURE		PESO WEIGHT			KIT RICAMBIO REPAIR KIT	
			MPa	psi	g	oz			pz / pcs
4073500016	G 1/2 F	G 1/2 F	10-25	1450-3630	1260	44,45	1	4079900057	1
4073500003	G 1/2 F	G 1/2 F	20-50	2900-7250	1480	52,21	1	4079900048	1



INDICE: **Valvole di massima pressione**
 INDEX: Maximum pressure valves

CATEGORIA: **Max 66 MPa**
 CATEGORY:

ARTICOLO:
 PRODUCT NAME:

SVL60

PRESSIONE AMMISSIBILE/PERMISSIBLE PRESSURE 660 bar 66 MPa 9570 psi
PORTATA NOMINALE/RATED FLOW 100 l/min 26,4 USGpm
TEMPERATURA NOMINALE/RATED TEMPERATURE 90 °C 194 °F

CODICE CODE	ENTRATA INLET	BY-PASS	INTERVALLO DI TARATURA ALLOWABLE SETTING PRESSURE		PESO WEIGHT			KIT RICAMBIO REPAIR KIT	
			MPa	psi	g	oz			pz / pcs
4073201006	G 3/8 F	G 1/2 F	25-60	3630-8700	1650	58,20	1	4079900068	1



OTTONE NICHELATO
 NICKEL PLATED BRASS

AISI 316

13

INDICE: **Valvole di massima pressione**
 INDEX: Maximum pressure valves

CATEGORIA: **Max 72 MPa**
 CATEGORY:

ARTICOLO:
 PRODUCT NAME:

SVL70

PRESSIONE AMMISSIBILE/PERMISSIBLE PRESSURE 720 bar 72 MPa 10450 psi
PORTATA NOMINALE/RATED FLOW 60 l/min 16 USGpm
TEMPERATURA NOMINALE/RATED TEMPERATURE 90 °C 194 °F

CODICE CODE	ENTRATA INLET	BY-PASS	INTERVALLO DI TARATURA ALLOWABLE SETTING PRESSURE		PESO WEIGHT			KIT RICAMBIO REPAIR KIT	
			MPa	psi	g	oz			pz / pcs
4073201005	G 3/8 F	G 1/2 F	28 - 40	4060 - 5800	2000	70,55	1	4079900033	1
4073201004	G 3/8 F	G 1/2 F	40 - 50	5800 - 7250	2000	70,55	1	4079900033	1
4073201003	G 3/8 F	G 1/2 F	50 - 66	7250 - 9570	2000	70,55	1	4079900033	1
4073201002	Rc 3/8 F	G 1/2 F	28 - 40	4060 - 5800	2000	70,55	1	4079900033	1
4073201001	Rc 3/8 F	G 1/2 F	40 - 50	5800 - 7250	2000	70,55	1	4079900033	1
4073201000	Rc 3/8 F	G 1/2 F	50 - 66	7250 - 9570	2000	70,55	1	4079900033	1



OTTONE NICHELATO
 NICKEL PLATED BRASS

INOX AISI 303
 STAINLESS STEEL AISI 303

Rc = filetto conico/conic thread
 G = filetto cilindrico/cylindrical thread

INDICE: **Valvole di massima pressione**
 INDEX: Maximum pressure valves

CATEGORIA: **Max 90 MPa**
 CATEGORY:

ARTICOLO:
 PRODUCT NAME:

SVL80

OTTONE NICHELATO
 NICKEL PLATED BRASS

INOX AISI 303
 STAINLESS STEEL AISI 303



PRESSIONE AMMISSIBILE/PERMISSIBLE PRESSURE 900 bar 90 MPa 13050 psi
PORTATA NOMINALE/RATED FLOW 60 l/min 16 USGpm
TEMPERATURA NOMINALE/RATED TEMPERATURE 90 °C 194 °F

CODICE CODE	ENTRATA INLET	BY-PASS	INTERVALLO DI TARATURA ALLOWABLE SETTING PRESSURE		PESO WEIGHT			KIT RICAMBIO REPAIR KIT	
			MPa	psi	g	oz			pz / pcs
4073201008	G 3/8 F	G 1/2 F	66 - 80	9570 - 11600	2000	70,55	1	4079900072	1
4073201009	Rc 3/8 F	G 1/2 F	66 - 80	9570 - 11600	2000	70,55	1	4079900072	1

Rc = filetto conico/conic thread

G = filetto cilindrico/cylindrical thread

INDICE: **Valvole di massima pressione**
 INDEX: Maximum pressure valves

CATEGORIA: **Max 20 MPa**
 CATEGORY:

ARTICOLO:
 PRODUCT NAME:

SVL20/250



PRESSIONE AMMISSIBILE/PERMISSIBLE PRESSURE 200 bar 20 MPa 2900 psi
PORTATA NOMINALE/RATED FLOW 250 l/min 66 USGpm
TEMPERATURA NOMINALE/RATED TEMPERATURE 90 °C 194 °F

CODICE CODE	ENTRATA INLET	BY-PASS	INTERVALLO DI TARATURA ALLOWABLE SETTING PRESSURE		PESO WEIGHT			KIT RICAMBIO REPAIR KIT	
			MPa	psi	g	oz			pz / pcs
4073500006	G 3/4 F	G 3/4 F	8 - 18	1160 - 2610	1140	40,21	1	4079900052	1

INDICE: **Valvole di massima pressione**
 INDEX: Maximum pressure valves

CATEGORIA: **Max 33 MPa**
 CATEGORY:

ARTICOLO:
 PRODUCT NAME:

SVL22/450
SVL33/450



PRESSIONE AMMISSIBILE/PERMISSIBLE PRESSURE 330 bar 33 MPa 4800 psi
PORTATA NOMINALE/RATED FLOW 450 l/min 120 USGpm
TEMPERATURA NOMINALE/RATED TEMPERATURE 90 °C 194 °F

CODICE CODE	ENTRATA INLET	BY-PASS	INTERVALLO DI TARATURA ALLOWABLE SETTING PRESSURE		PESO WEIGHT			KIT RICAMBIO REPAIR KIT	
			MPa	psi	g	oz			pz / pcs
4073500001	G 1" F	G 1" F	10 - 20	1450 - 2900	4650	164	1	4079900036	1
4073500002	G 1" F	G 1" F	15 - 30	2175 - 4350	4800	169	1	4079900036	1