

# B758 TRACK FELLER BUNCHER



## POWERFUL PERFORMANCE.

Powerful combination of lift capacity, swing torque, and tractive effort provides for maximum machine performance, increasing overall machine efficiency and operator experience in adverse terrain and large timber.



## UNOBSTRUCTED GROUND CLEARANCE.

High, unobstructed carbody enables un-impeded travel over rocks, stumps, and other debris with 35" (889 mm) of ground clearance. Leveling cylinders do not extend below the bottom surface of the carbody.



## PURPOSE BUILT LOWER FRAME.

Extended, eleven roller track frames provide maximum stability and lift capacity, while minimizing ground pressure. Variable gauge roller frames provide flexibility in machine width, for over-the-side stability or transport.



## STEEP SLOPE OPTIONS.

Purpose-built steep slope harvesting options include specialized engine and hydraulic kits and a cable-assist mount, which improve operator comfort, productivity and efficiency, and ensure reliable machine performance.



## PROVEN RELIABILITY AND DURABILITY.

Extensive validation of common key components that includes the engine, hydraulic pumps, swing drive, and grease-lubricated Cat® 349 HD HEX undercarriage ensure machine uptime and reduce overall operating costs.



## EXCELLENT SERVICEABILITY.

Gull-wing engine enclosures provide unmatched serviceability of components and enables "walk-through" engine access from the cab side of the machine. Enclosures provide a flat area to complete preventative maintenance and service.

# B758 SPECIFICATIONS

<b>Engine Model</b>	Cat® C9 Tier 3	<b>Tractive Effort</b>	104,000 lb 47 174 kg	<b>Fuel Tank Capacity</b>	312 gal 1181 L
<b>Gross Power</b>	303 hp 226 kW	<b>Undercarriage Size</b>	349 HD HEX	<b>Engine Oil Capacity</b>	10.3 gal 39 L
<b>Engine Displacement</b>	537 in³ 8.8 L	<b>Undercarriage Pitch</b>	8.5" 216 mm	<b>Hydraulic System Capacity</b>	97.7 gal 370 L
<b>Weight (no head)</b>	81,738 lb 37 076 kg	<b>Ground Clearance</b>	35" 889 mm	<b>Transport Width</b>	11' 10" 3.61 m
<b>Maximum Flow</b>	250 gpm 946 L/min	<b>Track Gauge</b>	113" 2870 mm	<b>Height</b>	13' 0" 3.96 m
<b>Max. Reach (w/ 201 saw)</b>	28' 1" 8.56 m	<b>Track Length</b>	221" 5615 mm	<b>Length (boom ext., w/201 saw)</b>	39' 8" 12.10 m
<b>Lift at Max. Reach (no head)</b>	19,111 lb 8669 kg	<b>Leveling System Capability</b>	21° Forward 11° Side-to-Side	<b>Length (boom tuck., no head)</b>	32' 2" 9.81 m

Base configuration includes standard feller buncher boom and stick, roller frames in the wide position, and 28" (710 mm) single grouser shoes.

## POWERTRAIN

Cat C9 engine certified to EPA Tier 3  
 Primary, secondary, and tertiary fuel filters, including water separator  
 Electric fuel priming pump  
 Side-by-side radiator and oil cooler  
 Swing out air-to-air cooler and air conditioner condenser  
 Removable debris screen  
 Centrifugal engine air pre-cleaner  
 Under-hood 2-stage engine air cleaner  
 Variable pitch, reversing fan with guard  
 Heavy-duty starter and ether aid

## UNDERCARRIAGE

Three-cylinder leveling system  
 Heavy-duty variable gauge track roller frames  
 Grease-lubricated 349 HD HEX track  
 Straddle mounted carrier rollers  
 Heavy-duty bottom track rollers (11 per side)  
 Heavy-duty recoil mechanisms  
 Full length track shoe support  
 Heavy-duty travel motor and swivel guards  
 Towing eyes on base frame

## HYDRAULICS

2 main hydraulic pump groups for track and implement functions  
 Saw pump for feller buncher and intermittent saw hydraulics only  
 High-performance hydraulic return filters  
 325 size, high torque swing drive  
 Swing cushion valve and automatic swing parking brake  
 Two speed auto-shift travel  
 Electric hydraulic oil fill pump  
 Spare hose storage area

## ELECTRICAL

95 ampere alternator  
 24-volt electrical system with 2 12-volt batteries  
 10 LED working lights and 3 LED service lights  
 Horn and travel alarm  
 Secondary engine shut off switch  
 Product Link™ ready

## SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry dealers worldwide

[WEILERFORESTRY.COM](http://WEILERFORESTRY.COM)

## OPERATOR ENVIRONMENT

Enclosed FOPS/ROPS/OPS/OR-OSHA/WCB certified cab  
 Seat with air suspension, integrated joysticks, and head rest  
 Retractable 4-point seat belt  
 Display monitor and programmable operator controls  
 Scratch resistant polycarbonate windows  
 Reverse slope 1.25" (32 mm) front windshield  
 Skylight with sun shade  
 Windshield wiper and washer  
 Left-side fresh air window  
 Pressurized cab with filtered ventilation and forced air fan  
 Heater / air conditioner / defroster with manual controls  
 Radio ready with speakers  
 Two sockets for 12-volt power supply

## OTHER STANDARD EQUIPMENT

Twin heavy-duty hood enclosure  
 Heavy-duty hood enclosure with machine level engine enclosure access  
 Heavy-duty doors, covers, and bottom guards

## OPTIONAL EQUIPMENT

Low or high flow standard feller buncher boom and sticks  
 Intermittent saw boom and stick  
 Short or long harvester boom and sticks  
 Boom and stick omission options  
 Standard or star carrier rollers  
 24" (600 mm) or 28" (710 mm) SG, 349 HD HEX Track  
 Cold or arctic weather starting aid  
 Engine and hydraulic steep slope kit and cable-assist mount  
 201 continuous saw w/ partial or full tilt - 22.5" (572 mm)

## WARRANTY

12 months standard, extended warranty available

Materials and specifications are subject to change without notice.  
 Featured machines and photos may include optional equipment. All rights reserved.

B758 LRC, SS (11-2019)