PATTERN CORRECTION - THE KNITTING BOOK

CABLED HAT

Page 280

PATTERN

HAT PATTERN

Using 5.5mm (UK5/US9) needles and cable cast-on method (see p.89), cast on 96sts.

Join into a round being careful not to twist cast on sts. Place marker at start of round.

Round 1: K1, *p2, k2, rep from * to last 3 sts, p2, k1.

Cont to rep last round until work measures 3.5cm (1%in).

Next round: Rib 2, *rib2tog, rib 5, rep from * to end, ending rib 3. (83sts)

WORK RIDGES

Rounds 1 and 2: P. Rounds 3 and 4: K.

Round 5: P.

Round 6: P3, *M1p, p6, rep from * to last 2sts, p2. (96 sts)

SET CABLE PATT

Change to 6mm (UK4/US10) needles and work in cable patt as follows:

Patt round 1: *P2, k2, p2, rep from * to end. Patt round 2: *P2, CR4L, rep from * to end.

Patt round 3: *P4, k2, rep from * to last 2sts. Place new start of round marker here.

Patt round 4: [CR4L, p2] x 16.

Patt round 5: *P2, k2, p2, rep from * to end, remove marker, p2, replace start of round marker.

Patt round 6: *CR4L, p2, rep from * to end. Previous 6 rows set pattern. Working in patt as set, continue rep these 6 rows until work measures 17cm (6¾in) from cast-on edge, ending with pattern row 6.

SHAPE TOP

Round 1: *P2tog, k2, p2, rep from * to end of round. (80sts)



Round 2: *P1, CR5L, slip next 2sts onto cable needle and leave at front of work, p2tog then k2 from cable needle, rep from * to end. (72sts)

Round 3: [P2, p2tog, k2, p1, k2] x 8. (64sts)

Round 4: [P1, p2tog, CR5L] x 8. (56sts)

Round 5: [P1, p2tog, p2, k2] x 7, p1, p2tog, p2, move start of round marker to here (48sts).

Round 6: [Slip next 2sts onto cable needle and leave at front of work, p3, then k2tog tbl from cable needle, p1] x 8. (40sts)

Round 7: [P3, k2tog tbl] x 7, p3, move start of round marker to here. (32sts)

Round 8: Slip 2 sts onto cable needle and leave at front of work, p2tog, k2tog tbl from cable needle, p1, *slip next stitch onto cable needle and leave at front of work, p2tog, k1 tbl from cable needle, p1, rep from * to end of round.

Round 9: [K2tog tbl, p1] x 8. (16sts)

Draw yarn through rem sts and fasten off. Darn in ends.