



LIGNUM ADDITIONS

Lignum Additions Comfort 2mm

Comfort standard offers an economic solution for insulating laminate floors. Comfort is produced from closed cell Polyethylene Foam which is CFC and HCFC free and 100% recyclable. The product is available in various sizes to suit most applications. Minor floor imperfections may be accommodated by using these materials. The product has very effective acoustic qualities.

- Excellent impact sound insulation
- Absorbs minor floor imperfections
- Non dusting, non-toxic and odourless
- Lightweight
- Easy to lay
- CFC and HCFC free



Dimensions: 2mm x 1m x 25m

Technical Specification

Properties	Typical Value	Method
Roll Specifications		
Nominal Thickness	2mm \pm 10%	ISO 1923
Width	1m \pm 1%	ISO 1923
Length	\pm 1%	ISO 1923
Roll Weight	40 g/m ²	
Apparent Density	\approx 20 kg/m ³	ISO 845
Acoustic Properties		
Sound Reduction	Not Tested	
Thermal Properties		
Thermal Conductivity (λ) Tested at mean 10°C	0.049 W/mK	BS 4745:2005
Thermal Resistance (R – Value)	0.041 m ² K/W	BS 4745:2005
TOG	0.41	BS 4745:2005
Foam Colour / Backing	White / No Backing	

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.