

PRODUCT DESCRIPTION

Lignum Strata Twenty/6 Premium

Engineered Wooden Flooring

PROPERTY	INFORMATION
Dimension	2200 x 190 x 20 mm Top layer > 6.0 mm
Packing	Pack quantity = 2.376m ² 40cartons per pallet = 95.04m ²
Production	Multi-ply construction
Laying	Tongue & groove Can be laid as floating floor, stuck down or nailed (see instructions)



CLASSIFICATION SPECIFICATIONS

FACTOR	STANDARD	COMMENTS
Resistance to roller castor chairs	EN 425	Use of conventional chairmat recommended
Effect of furniture legs	EN 424	No visible change
Thermal conductivity	EN 12664	0.077 m ² K/W
Formaldehyde	EN 717-1	≤ 0.05 ppm
Disposal		Private waste disposal with regular household waste acceptable
Suitability for underfloor heating		Suitable up to 27°C

SURFACE PROPERTIES

Slip resistance	EN 13893	$\mu \geq 0.47$
Resistance to fire	EN 13501-1	D _{f1} s1
Chemical resistance	EN 13442	Category 5

Wood Innovations 52 Newry Road, Warrenpoint, County Down, N. Ireland. BT34 3LD

Tel: 028 4177 3366

Email: sales@woodinnovations.co.uk www.woodinnovations.com