



A90 Intelligent GNSS Receiver



- **Compact design, more productive**
- **Professional GNSS satellites tracked simultaneously! GPS, Glonass, Galileo, Beidou |**
- **Automatic data collection during centering**
- **IMU tilt function is adopted, A90 still could get the right point data by automatic correct system**
- **Applies WIFI connection to realize WebUI control designed to modify settings and monitor the receiver status**
- **Bundled Android field software brings a big change in use experience and accessibility**

A90 GNSS Receiver Specifications

GNSS Engine

- 555 channels
- Advanced interface detection and mitigation
- Maximum data rate: 100Hz
- GPS: L1C/A, L1C, L2C, L2P, L5
- GLONASS: L1C/A, L2C/A, L2P, L3, L5
- BeiDou: B1, B2, B3
- Galileo: E1, E5 AltBOC, E5a, E5b, E6
- NavIC (IRNSS): L5
- SBAS: L1, L5
- QZSS: L1 C/A, UC, L2C, L5, L6
- L-Band: Up to 5 channels
- Performance Specifications
- Time to First Fix (TTFF):
- Cold start: $40s$ (typical)
- Hot start: $19s$ (typical)
- Signal reacquisition:
- L1 $0.5s$ (typical)
- L2 $1.0s$ (typical)

" RTK Initialization time:

- $10s$
- RTK Initialization reliability:
- Egg g*/,

Real-Time Accuracy (rms)

- SBAS
- Horizontal: 60cm (1.97ft), Vertical: 120cm (3.94ft)
- Real-Time DGPS position
- Horizontal: 40cm (1.31ft), Vertical: 80cm (2.62ft)
- Real-Time Kinematic Position (fine mode)
- Horizontal: 8mm (0.03ft) + 0.5 ppm
- Vertical: 15 mm (0.05ft) + 0.5 ppm
- Post Processing Accuracy (rms) " 2
- Static, Rapid Static
- Horizontal 1.5 mm (0.005 ft) + 0.5 ppm
- Vertical 5 mm (0.016 ft) + 0.5 ppm
- Long Static
- Horizontal 3.0 mm (0.010ft) + 0.5 ppm
- Vertical 3.5 mm (0.011ft) + 0.5 ppm

Solutions

Field Software Suite FOIFPad (WM/Android), FOIF FieldGenius or Carlson SurvCE

- Main functions include:
- A90 GNSS Support: configuration, monitoring and control
- Volume computation
- Background raster image
- Network connectivity
- Coordinate System Support: predefined grid systems, predefined datums,
- projections, Geoids, local grid
- Map view with colored lines
- Geodetic Geometry: intersection, azimuth/distance, offsetting, poly-line,
- curve, area
- Road Construction(3D)
- Survey Utilities: calculator, RW5 file
- viewing
- Data import/Export: DXF, SHP, RW5

Data logging

- Recording Interval
- 0.1-999seconds
- Physical
- " Flat design
- " Size: 156mm*76mm(@ xH)
- " Bottom cover: Aluminium magnesium alloy
- Memory
- Internal memory: 8GB standard; Supports extending to 32GB
- I/O Interface
- TNC port: connecting built-in radio antenna
- 5-pin lemo port: connecting external power supply and external radio
- 7-pin lemo port (USB+serial port): connecting PC and handheld
- Operating system
- Based on Linux; Supports Web UI
- Voice
- Multi-language supported
- Tilt survey sensor
- Automatic correct system by 30degree
- Data Format
- RTCM 2.3
- RTCM 3.0, RTCM3.X "
- CMR, CMR+
- " NovAtelX/SCMRx

RTK rover/base, post-processing

- " RTK Network rover: VRS, FKP, MAC
- " Point-to-Point GPRS through Real-timeData " server Software (internal GPRs or external cell phone)

- LandXML (FOIF FieldGenius support)
- Total Station support (FOIF FieldGenius)
- Import and stake directly from a DXF File (FOIF FieldGenius)

Office Software Suite:

- FOIF Geomatics office Main functions include:
- Network post-processing
- Integrated transformation and grid system computations
- Pre-defined datums along with use -defined capabilities
- Survey mission planning
- Automatic vector processing
- Least-squares network adjustment
- Data analysis and quality control tools
- Coordinate transformations
- Reporting
- Exporting
- Geoid

Environmental (MIL810F)

- Operating temperature:
- 30°C to +65°C (22°F to 149°F)
- Storage temperature:
- 40°C to +80°C (-40°F to +176°F)

- " Humidity: 100% condensing
- " Waterproof: IP68 and MIL-810G standard "
- Shock: 2 m (6.56 ft) pole drop
- 1.2m (3.94ft) free drop

Power

- 7.2V, 6800mAh, removable battery
- Optional System Components
- Communication Module
- Internal radio
- UHF-Link (410-470MHz) Rx/ErTx both -1W
- External radio
- FOIF external radio Rx/ErTx (FDL-5, 5/35W selectable)
- 4G LTE module:
- Fits various networks
- BlueTooth
- 2.1+EDR Class 2
- WiFi
- IEEE 802.11 b/g/n
- Antenna
- Built-in antenna, integrating GNSS, BT/WLAN and network antenna
- Controller
- F58

*1 Performance values assume minimum off five satellites, following the procedures recommended in the product manual. High-multipath areas, high PDOP values and periods of severe atmospheric conditions may degrade performance.
*2 Long baselines, long occupations, precise ephemeris used.

FOIF Geomatics CAD

- Main functions include:
- DWG file format, compatible with AutoCAD
- Integrated transformation and grid system computations
- Full 3D least squares adjustment, blunder detection, graphical ellipse display
- DTM contouring/Modeling volumes/3D rendering
- Site Design: Ponds, ditches, stockpiles and slopes
- Road Design: horizontal and vertical alignments, cross sectional templates
- Completely customizable user interface
- Toolbars - can be arranged with "drag and drop" functionality
- Menu - can be re-organized with our graphical menu editor
- Screen - items can be turned off for more graphics area
- Lay out - of command window - top or bottom
- Reporting, exporting and printing

Related Products



A30 Receiver



A60 Receiver



A3 Static Receiver



A50 Receiver



Fs8 GNSS Handheld



A LOO Reference Receiver



A200 CORS Receiver

Illustrations, descriptions and technical specifications are not binding and may change



Since 1958

Janak Positioning & Surveying Systems Pvt. Ltd.

"Ram Group" 304-B, Pal Mohan Plaza, 11/56,
D.B. Gupta Road, Karol Bagh,
New Delhi-110005

Phone: 011-23515400, 23515399, 23617190
Fax: 011-23682185 ; Mobile: +91-9811008317

janak.ji@yahoo.com
www.janakindia.com

Local Dealer:



JANAK
POSITIONING &
SURVEYING