ExTell Atom+ Line Interactive UPS 2000VA

Reference Standard- Safety -IEC/EN 62040-1

Product Overview

ExTell Atom+ Series is a Line Interactive UPS Series that ranges from 600VA to 3000VA. Atom+ comes with Built-In internal VRLA Batteries to support customer applications. Atom+ Series UPS features a super smart charger that reduces charging time for the batteries.

Atom+ has a Auto-Restart function while the AC power is recovering leading to quick boot up for supporting any critical applications. With a built In self diagnostic function and self test upon powering on, the LCD Display quickly conveys advanced information about the UPS to keep customers updated on the functioning of the device.

Atom+ is the ideal UPS device for applications such as CCTV, NVR Backup, Desktop and other SOHO applications.



Features

- Cold Start Function
- LCD Display
- Compact Size
- 600VA to 3000VA
- AVR for Voltage Stabilization
- Simulated Sinewave output
- UK Output Power Socket



 © 2016 ExTell Systems. All rights reserved.

ExTell Atom+ Line Interactive UPS 2000VA

Reference Standard- Safety -IEC/EN 62040-1

Technical Specifications

Model	EAP-2000-UK
Capacity	2000VA/1200W
Input	
Nominal Voltage	220/230/240 VAC
Voltage Range	162 - 290VAC
Frequency Range	50 or 60 Hz (Auto Sensing)
Output	
Voltage Regulation	AC Mode - 220/230/240 VAC ± 10% / Battery - 230VAC
Frequency	50/60Hz (Auto sensing)
Waveform	Simulated Sinewave
Transfer Time	2-6 ms, 10ms Max
Outlet Configuration	UK Type Outlets
Battery	
Voltage	24V DC
Type	12V/9Ah x 2PC
Recharge Time	4-6 hours to 90% after Complete Discharge
Safety Protection	Over Charge and Over Discharge Protection
Advanced Battery Management	Yes
Display	
LCD Display	Input and Output Voltage & Frequency Load% Battery%
Audible Alarm	
Battery Mode	Short tones every 8 seconds
Low Battery	Short tones every second
Overload	Short tones every 0.5 second
Fault	Beeping Continuously
Management	
Smart USB	USB or RS232(Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC)
Environment	
Operating Temp	0 ~ 40°C
Relative Humidity	0 ~ 90% non-condensing
Accoustic Noise	<45db at 1M
Physical	
Dimensions	140 (W) * 320 (D) * 185 (H) mm
Weight	6.5 kg

ExTell Systems Corporation · DE, USA. Product Specifications subject to routine updates.
Reach out to: support@extellsystems.com for Product clarifications. © 2016 ExTell Systems. All rights reserved.

Middle East
UAE: +971 6 779 4299
sales.imea@extellsystems..com

Middle East
Bahrain/KSA: +973 77 936 545
sales.imea@extellsystems..com

India
+91 808 62 77222
sales.imea@extellsystems..com

North America
+1 404 326 4101
sales@extellsystems.com