

Cisco Config 5 Secondary Power Supply - power supply - hot-plug - 125 Watt(PWR-C5-125WAC=)

Cisco Config 5 Secondary Power Supply - Power supply - hot-plug (plug-in module) - AC 100-240 V - 125 Watt - for P/N: C9200-24T-A, C9200-24T-E, C9200-48T-A, C9200-48T-E, C9200-48T-EDU, C9200L-48T-4G-E-WS

The Cisco Config 5 Secondary Power Supply represents a strategic investment in your network's operational efficiency and reliability. Designed to complement your existing network hardware, this plug-in module ensures smooth integration and enhanced performance. Its compatibility with a wide range of network hardware makes it a versatile solution for any setup, aiming to provide uninterrupted power supply and minimize downtime. With its focus on reliability and ease of use, the Cisco Config 5 Secondary Power Supply is an essential component for maintaining a robust network infrastructure.

Key Selling Points

- Plug-in module form factor for easy installation
- Compatible with network hardware for seamless integration

Product Features

- Enhanced reliability**
The Config 5 Secondary Power Supply by Cisco is designed as a plug-in module, ensuring easy installation and a secure fit into network hardware. Its compatibility with network hardware makes it a versatile addition to enhance system reliability and performance.
- Seamless integration**
This power supply unit integrates with your existing network hardware, providing an efficient power solution without the need for extensive modifications or upgrades. Its design prioritizes both functionality and ease of use, making it an ideal choice for maintaining uninterrupted network operations.

Main Specifications

Product Description	Cisco Config 5 Secondary Power Supply - power supply - hot-plug - 125 Watt
Device Type	Power supply - hot-plug - plug-in module
Weight	680 g
Input Voltage	AC 100-240 V
Output Voltage	12 V
Power Capacity	125 Watt
Input Connectors	Power IEC 60320 C14
Dimensions (WxDxH)	10.2 cm x 19.3 cm x 4.01 cm
Designed For	P/N: C9200-24T-A, C9200-24T-E, C9200-24T-EDU, C9200-48T-A, C9200-48T-E, C9200-48T-EDU, C9200L-24T-4G-A, C9200L-24T-4G-EDU, C9200L-24T-4X-A, C9200L-24T-4X-E, C9200L-24T-4X-EDU, C9200L-48T-4G-A, C9200L-48T-4G-E, C9200L-48T-4G-EDU, C9200L-48T-4G-E-WS, C9200L-48T-4X-A, C9200L-48T-4X-E, C9200L-48T-4X-EDU

Extended Specification

General

Device Type	Power supply - hot-plug - plug-in module
-------------	--

Miscellaneous

Compliant Standards	FCC CFR47 Part 15 B Class A, ICES-003 Class A, EN 55032 Class A, CISPR 32 Class A, AS/NZS 3548 Class A, BSMI Class A, VCCI Class A, CISPR 35, EN55024, EN 300 386, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, UL 60950-1, CAN/CSA-C22.2 No. 60950-1, EN 60950-1, IEC 60950-1, CCC
---------------------	--

Environmental Parameters

Min Operating Temperature	-5 °C
Max Operating Temperature	45 °C
Humidity Range Operating	5 - 90% (non-condensing)

Power Device

Input Voltage	AC 100-240 V
Frequency Required	50 - 60 Hz
Input Connectors	Power IEC 60320 C14
Output Voltage	12 V
Max Electric Current	10.5 A
Power Capacity	125 Watt

Dimensions & Weight

Width	10.2 cm
Depth	19.3 cm
Height	4.01 cm
Weight	680 g

Compatibility Information

Designed For	P/N: C9200-24T-A, C9200-24T-E, C9200-24T-EDU, C9200-48T-A, C9200-48T-E, C9200-48T-EDU, C9200L-24T-4G-A, C9200L-24T-4G-E, C9200L-24T-4G-EDU, C9200L-24T-4X-A, C9200L-24T-4X-E, C9200L-24T-4X-EDU, C9200L-48T-4G-A, C9200L-48T-4G-E, C9200L-48T-4G-EDU, C9200L-48T-4G-E-WS, C9200L-48T-4X-A, C9200L-48T-4X-E, C9200L-48T-4X-EDU
--------------	---

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet