

Cisco Config 1 - power supply - hot-plug / redundant - 350 Watt(PWR-C1-350WAC-P=)

Cisco Config 1 - Power supply - hot-plug / redundant (plug-in module) - 80 PLUS Platinum - AC 100-240 V - 350 Watt - for Catalyst 9300 (350 Watt), 9300L (350 Watt)

The Cisco Config 1 power supply is a significant step forward in power management for network systems. Designed as a hot-plug and redundant power supply, it ensures that your network hardware remains operational, with minimal downtime. This plug-in module is not only easy to install and remove but also compatible with a wide range of network hardware, making it a versatile choice for any setup. With a voltage output of -56 V, it provides efficient power distribution to keep your systems running smoothly. Whether you're looking to upgrade your current setup or build a new one, the Cisco Config 1 power supply offers the reliability and efficiency your network needs.

Key Selling Points

- Hot-plug and redundant design for continuous operation
- Plug-in module form factor for easy integration
- Optimized for network hardware compatibility
- Provides -56 V of power to ensure efficient operation

Product Features

**Reliable power supply**  
Designed for critical network hardware, this power supply ensures your systems stay operational with its hot-plug and redundant capabilities, minimizing downtime and maintaining business continuity.

**Efficient operation**  
The plug-in module form factor is engineered for easy installation and removal, providing a seamless integration with your network hardware. Its -56 V output is optimized for efficient power distribution, ensuring your equipment runs smoothly.

Main Specifications

Product Description	Cisco Config 1 - power supply - hot-plug / redundant - 350 Watt
Device Type	Power supply - hot-plug / redundant - plug-in module
80 PLUS Certification	80 PLUS Platinum
Weight	1.2 kg
Input Voltage	AC 100-240 V
Output Voltage	-56 V
Power Capacity	350 Watt
Input Connectors	Power IEC 60320 C14
Dimensions (WxDxH)	8.26 cm x 31 cm x 4.01 cm
Designed For	Catalyst 9300 (350 Watt), 9300L (350 Watt)

Extended Specification

General

Device Type	Power supply - hot-plug / redundant - plug-in module
-------------	--

Environmental Parameters

Min Operating Temperature	-5 °C
Max Operating Temperature	45 °C
Humidity Range Operating	5 - 90% (non-condensing)

**Power Device**

Input Voltage	AC 100-240 V
Frequency Required	50 - 60 Hz
Input Connectors	Power IEC 60320 C14
Output Voltage	-56 V
Power Capacity	350 Watt
80 PLUS Certification	80 PLUS Platinum

**Dimensions & Weight**

Width	8.26 cm
Depth	31 cm
Height	4.01 cm
Weight	1.2 kg

**Compatibility Information**

Designed For	Cisco Catalyst 9300 (350 Watt), 9300L (350 Watt)
--------------	--

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet