

Cisco Config 2 Secondary Power Supply - power supply - hot-plug - 600 Watt(PWR-C5-600WAC=)

Cisco Config 2 Secondary Power Supply - Power supply - hot-plug (plug-in module) - 600 Watt - for P/N: C9200-24P-EDU, C9200-24P-E-WS, C9200L-24P-4G-E-WS, C9200L-24P-4X-E-WS

The 1025-W power supply module is an auto-ranging unit that supports input voltages between 115 and 240 VAC. The power supply module has internal fans. All switches ship with a blank cover in the second power supply slot.

Key Selling Points

- Plug-in module form factor for easy installation
- Compatible with network hardware, offering versatile use
- Designed to minimize downtime and maintain productivity
- Ensures a stable and continuous power supply

Product Features

Enhanced reliability

The Config 2 Secondary Power Supply by Cisco is designed as a plug-in module, ensuring easy installation and removal without disrupting the network hardware's operation. Its compatibility with network hardware makes it a versatile addition to any setup, providing a reliable power source that minimizes downtime and maintains productivity.

Seamless integration

This power supply's form factor is meticulously crafted to fit seamlessly into your existing network infrastructure. Its design not only complements Cisco network hardware but also enhances the overall efficiency of the system by ensuring a stable and continuous power supply.

Main Specifications

Product Description	Cisco Config 2 Secondary Power Supply - power supply - hot-plug - 600 Watt
Device Type	Power supply - hot-plug - plug-in module
Power Capacity	600 Watt
Designed For	P/N: C9200-24P-A, C9200-24P-E, C9200-24P-EDU, C9200-24P-E-WS, C9200L-24P-4G-A, C9200L-24P-4G-A=, C9200L-24P-4G-E, C9200L-24P-4G-EDU, C9200L-24P-4G-E-WS, C9200L-24P-4X-A, C9200L-24P-4X-E, C9200L-24P-4X-EDU, C9200L-24P-4X-E-WS

Extended Specification

General

Device Type	Power supply - hot-plug - plug-in module
-------------	--

Power Device

Power Capacity	600 Watt
----------------	----------

Compatibility Information

Designed For	P/N: C9200-24P-A, C9200-24P-E, C9200-24P-EDU, C9200-24P-E-WS, C9200L-24P-4G-A, C9200L-24P-4G-A=, C9200L-24P-4G-E, C9200L-24P-4G-EDU, C9200L-24P-4G-E-WS, C9200L-24P-4X-A, C9200L-24P-4X-E, C9200L-24P-4X-EDU, C9200L-24P-4X-E-WS
--------------	--