

## Cisco - power supply - hot-plug(PWR-RGD-AC-DC-H=)

## Cisco - Power supply - hot-plug (plug-in module) - AC 100-240/ DC 100-250 V - for Industrial Ethernet 5000 Series

The Cisco power supply is a high-performance, hot-plug module designed to meet the needs of demanding network environments. With its robust compatibility with PC network hardware, it offers a reliable solution for maintaining operational efficiency. The power supply supports a wide input voltage range, ensuring adaptability to both AC and DC power sources. Its ability to operate in extreme temperature conditions, from -40°C to 60°C, and to withstand humidity levels of 5 - 95% (non-condensing), makes it an ideal choice for a variety of operational settings. Whether upgrading existing infrastructure or setting up new installations, this Cisco power supply module provides the flexibility and reliability needed to support critical network operations.

### Key Selling Points

- Plug-and-Play module form factor for easy installation
- Supports a wide frequency range of 47 - 63 Hz
- Operates efficiently within a wide temperature range
- Compatible with a variety of network hardware

### Product Features

#### Robust compatibility

Designed to seamlessly integrate with network hardware, this power supply ensures reliable performance across a wide range of devices.

#### Wide operating range

With an operating temperature range from -40°C to 60°C and humidity tolerance from 5 - 95% (non-condensing), it's built to withstand harsh environments.

#### Flexible power input

Accommodates a broad input voltage range of AC 85 - 264 / DC 88 - 300 V, making it versatile for various power setups.

### Main Specifications

Product Description	Cisco - power supply - hot-plug
Device Type	Power supply - hot-plug - plug-in module
Weight	1.15 kg
Input Voltage	AC 100-240/ DC 100-250 V
Dimensions (WxDxH)	17.8 cm x 12.7 cm x 4 cm
Designed For	Industrial Ethernet 5000 Series

### Extended Specification

#### General

Device Type	Power supply - hot-plug - plug-in module
-------------	--

#### Environmental Parameters

Min Operating Temperature	-40 °C
Max Operating Temperature	60 °C
Humidity Range Operating	5 - 95% (non-condensing)

#### Power Device

Input Voltage	AC 100-240/ DC 100-250 V
---------------	--------------------------

Input Voltage Range	AC 85 - 264 / DC 88 - 300 V
Frequency Required	47 - 63 Hz

#### Dimensions & Weight

Width	17.8 cm
Depth	12.7 cm
Height	4 cm
Weight	1.15 kg

#### Compatibility Information

Designed For	Cisco Industrial Ethernet 5000 Series
--------------	---------------------------------------

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet