

Cisco - power supply - hot-plug / redundant(ASR-920-PWR-A=)

Cisco - Power supply - hot-plug / redundant (plug-in module) - AC 85-264 V - for ASR 920

The Cisco power supply is engineered to meet the rigorous demands of today's network infrastructure, offering hot-plug and redundant capabilities to ensure your systems remain operational without interruption. This plug-in module is designed to be compatible with PC network hardware, making it a versatile addition to any setup. With a remarkable MTBF of 356,809 hours, it promises reliability and performance. Furthermore, it supports a broad input voltage range of AC 85 - 264 V and operates efficiently across different power conditions with a frequency requirement of 47 - 63 Hz. Whether upgrading existing equipment or setting up a new network, this power supply is built to deliver consistent, efficient power.

Key Selling Points

Hot-plug and redundant capabilities for enhanced reliability
Supports a wide input voltage range of AC 85 - 264 V
Compatible with network hardware, ensuring seamless integration
High MTBF of 356,809 hours for long-lasting performance

Product Features

Reliable performance

Designed for continuous operation, the power supply boasts an impressive MTBF (Mean Time Between Failures) of 356,809 hours, ensuring dependable performance and minimizing downtime for your network hardware.

Flexible compatibility

With its plug-in module form factor and compatibility with network hardware, this power supply offers a seamless integration experience, ensuring your PC and network infrastructure can maintain optimal power efficiency.

Versatile power range

Accommodating a wide range of input voltages from AC 85 - 264 V and frequencies from 47 - 63 Hz, this power supply ensures your network hardware operates efficiently across various power environments.

Main Specifications

Product Description	Cisco - power supply - hot-plug / redundant
Device Type	Power supply - hot-plug / redundant - plug-in module
Input Voltage	AC 85-264 V
Designed For	ASR 920

Extended Specification

General

Device Type	Power supply - hot-plug / redundant - plug-in module
-------------	--

Miscellaneous

MTBF	356,809 hours
------	---------------

Power Device

Input Voltage	AC 85-264 V
Frequency Required	47 - 63 Hz

Compatibility Information

Designed For	Cisco ASR 920
--------------	---------------