WD Ultrastar DC HC330 WUS721010ALE6L4 - hard drive - 10 TB - SATA 6Gb/s(0B42266)

WD Ultrastar DC HC330 WUS721010ALE6L4 - Hard drive - encrypted - 10 TB - internal - 3.5" - SATA 6Gb/s - 7200 rpm - buffer: 256 MB - Self-Encrypting Drive (SED)



As the industry evolves to develop purpose-built solutions for growing data storage requirements, IT managers continue to rely on mid-range capacity drives that are economical to acquire, yet deliver quick and reliable data access for traditional data center applications. Designed to handle workloads up to 550TB per year, the Ultrastar DC HC300 series is a proven air-platform design that delivers up to the industry leading capacity to help address the economic and access-density requirements of many data center workloads. Ideal for storage and server applications, as well as distributed and scalable computing (including block and file storage architectures), the Ultrastar DC HC300 series provides fast 7,200 RPM spindle speeds.

Key Selling Points

Higher capacity

Process data quickly with sustained transfer rates up to 255 MB/s

Reliable: enterprise-class 2M hours MTBF

Product Features

Enhanced durability

Designed for 24x7 operation and equipped with Rotational Vibration (RV) compensation technology, this hard drive ensures reliable performance in demanding environments. Its robust design supports up to 600,000 load/unload cycles, making it a durable choice for continuous use

High-capacity storage

With a generous 10 TB capacity, this hard drive meets the needs of data-intensive applications, offering ample space for large files and critical data. The advanced format 512e feature optimizes storage efficiency, allowing for more effective use of disk space.

Efficient data security

The Self-Encrypting Drive (SED) feature, coupled with hardware encryption, provides an added layer of security, safeguarding sensitive data against unauthorized access and ensuring data privacy.

Optimized power consumption

This hard drive is engineered for efficiency, with a typical power consumption of 9.2 W and an idle mode that reduces power usage to 8 W. This energy-efficient design helps lower operating costs while maintaining high performance.

High performance

Featuring a Serial ATA-600 interface for fast data transfer rates up to 600 MBps and an internal data rate of 260 MBps, this hard drive delivers swift and reliable data access. The average seek time of 8 ms and average latency of 4.16 ms ensure quick response times for demanding applications.

Main Specifications

| Product Description | WD Ultrastar DC HC330 WUS721010ALE6L4 - hard drive - 10 TB - SATA 6Gb/s |
|---------------------|---|
| Type | Hard drive - internal |
| Capacity | 10 TB |
| Hardware Encryption | Yes |
| Form Factor | 3.5" |
| Interface | SATA 6Gb/s |
| Data Transfer Rate | 600 MBps |
| Buffer Size | 256 MB |
| Spindle Speed | 7200 rpm |
| Features | Rotational Vibration (RV) compensation technology, Secure Erase function, advanced format 512e, 24x7 availability |
| Dimensions (WxDxH) | 101.6 mm x 147 mm x 26.1 mm |

Weight 750 g

Manufacturer Warranty 5-year warranty

Extended Specification

General

| Device Type | Hard drive - internal |
|---------------------|---|
| Capacity | 10 TB |
| Hardware Encryption | Yes |
| Form Factor | 3.5" |
| Interface | SATA 6Gb/s |
| Buffer Size | 256 MB |
| Bytes per Sector | 512 |
| Features | Rotational Vibration (RV) compensation technology, Secure Erase function, advanced format 512e, 24x7 availability |
| Width | 101.6 mm |
| Depth | 147 mm |
| Height | 26.1 mm |
| Weight | 750 g |

Manufacturer Warranty

Service & Support Limited warranty - 5 years

Miscellaneous

Compliant Standards RoHS

Power

Power Consumption 9.2 Watt (typical) | 8 Watt (idle)

Environmental Parameters

| Min Operating Temperature | 5 °C |
|---|-----------------------------|
| Max Operating Temperature | 60 °C |
| Min Storage Temperature | -40 °C |
| Max Storage Temperature | 70 °C |
| Shock Tolerance (operating) | 70 g @ 2 ms half-sine wave |
| Shock Tolerance (non- operating) | 250 g @ 2 ms half-sine wave |
| Vibration Tolerance (operating) | 0.67 g @ 5-500 Hz |
| Vibration Tolerance (non- operating) | 1.04 g @ 2-200 Hz |

Performance

| Drive Transfer Rate | 600 MBps (external) |
|---------------------|---------------------|
| Internal Data Rate | 260 MBps |
| Seek Time | 8 ms (average) |
| Average Latency | 4.16 ms |
| Spindle Speed | 7200 rpm |

Reliability

| MTBF | 2,000,000 hours |
|----------------|-----------------|
| 24x7 Operation | Yes |

| Non-Recoverable Errors | 1 per 10^15 |
|------------------------|-------------|
| Load / Unload Cycles | 600,000 |

Expansion & Connectivity

| Interfaces | 1 x SATA 6 Gb/s | |
|----------------|-----------------|--|
| Compatible Bay | 3.5" | |

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet