

StarTech.com HDMI Audio Extractor - 4K 60Hz - HDMI Audio De-embedder - HDR - Toslink Optical Audio - Dual RCA Audio - HDMI Audio (HD202A) - HDMI audio signal extractor(HD202A)

StarTech.com HDMI Audio Extractor - 4K 60Hz - HDMI Audio De-embedder - HDR - Toslink Optical Audio - Dual RCA Audio - HDMI Audio (HD202A) - HDMI audio signal extractor - black



This 4K HDMI audio extractor lets you de-embed the audio from your HDMI video streams to create a distinct audio output that you can connect directly to a digital or analog audio device. Supporting HDMI 2.0 specifications, the de-embedder maintains 4K 60Hz resolutions to deliver a seamless video experience.

The HDMI sound splitter supports video resolutions up to 4K 60Hz (3840 x 2160) and high video bandwidth up to 18Gbps. It also supports High Dynamic Range (HDR) video pass-through, letting you enjoy lifelike images with incredible contrast, brightness and color, and greater luminosity compared to standard digital imaging.

Easily integrate HDMI 2.0 devices, such as your new 4K Blu-ray player, with your existing audio equipment or desktop speakers. The extractor isolates and extracts the audio signal from your HDMI cable and lets you output to digital optical audio or dual RCA audio devices. The integrated EDID management capabilities support 2-channel, 5.1-channel and pass-through audio modes.

The HDCP compliant HDMI audio de-embedder is compatible with dual-RCA composite adapters, giving you the flexibility to integrate the audio from your HDMI source into 3.5 mm audio applications using MU6MMRCA, MU3MMRCA or MUFMRCA (sold separately).

The compact extractor features a small footprint that blends discreetly into your hardware setup, for a uniform look.

Key Selling Points

- Supports 4K 60 Hz HDMI input for video output
- Offers multiple audio output options including Toslink and RCA
- Made from durable aluminum for performance
- Includes mounting hardware for installation
- Operates in a temperature range suitable for environments

Product Features

- Versatile audio connections**
The HDMI audio extractor features multiple audio output types, including mini-phone 3.5 mm, RCA x 2, and SPDIF, enabling compatibility with audio equipment.
- Reliable performance**
This device is designed to operate effectively within a temperature range of 0 °C to 45 °C, ensuring performance in environments.
- Easy installation**
The package comes with mounting screws and brackets, facilitating installation and setup for both home and professional use.

Main Specifications

Product Description	StarTech.com HDMI Audio Extractor - 4K 60Hz - HDMI Audio De-embedder - HDR - Toslink Optical Audio - Dual RCA Audio - HDMI Audio (HD202A) - HDMI audio signal extractor
Product Type	HDMI audio signal extractor
Package Content	Power adapter, HDMI audio signal extractor, mounting screws, mounting brackets
Product Material	Aluminium
Dimensions (WxDxH)	8 cm x 9 cm x 2.2 cm
Weight	320 g
Colour	Black
Manufacturer Warranty	2-year warranty

Extended Specification

General

Product Type	HDMI audio signal extractor
Package Content	Power adapter, HDMI audio signal extractor, mounting screws, mounting brackets
Product Material	Aluminium
Width	8 cm
Depth	9 cm
Height	2.2 cm
Weight	320 g
Colour	Black

Manufacturer Warranty

Service & Support	2-year warranty
-------------------	-----------------

Miscellaneous

Power Source	AC power adapter
--------------	------------------

Connections

Connections	HDMI input - 19 pin HDMI Type A HDMI output - 19 pin HDMI Type A Audio line-out - mini-phone 3.5mm SPDIF output - TOS Link Component video/audio input - RCA x 2
-------------	--

Dimensions & Weight (Shipping)

Shipping Weight	400 g
-----------------	-------

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet