

Cisco Meraki MS130-8P - switch - 8 ports - Managed(MS130-8P-HW)

Cisco Meraki MS130-8P - Switch - Managed - 8 x 10/100/1000Base-T + 2 x Gigabit SFP - desktop, wall-mountable - PoE+ (120 W)



The Cisco Meraki MS130 switches provide Layer 2 access switching, ideal for branch and campus deployments. With 10 different models, capable of providing up to 740W of power over a variety of port densities, including SFP+ capable uplinks, the MS130 line is fully ready to support future wireless infrastructure deployments across a variety of different environments.

Key Selling Points

- More bandwidth
- Less overhead
- Zero-touch provisioning
- Power Over Ethernet (PoE)

Product Features

- SWITCH PORTS**
8 ports 1G + 2x 1GE SFP (total PoE power budget: 120W, PoE, PoE+)
- COMPACT FORM FACTOR**
Cisco Meraki MS130 switches provide Layer 2 access switching, ideal for branch and campus deployments
- EASE OF USE**
Choose Meraki cloud managed network switching for continuous network performance at scale without complexity

Main Specifications

Product Description	Cisco Meraki MS130-8P - switch - 8 ports - Managed
Device Type	Switch - 8 ports - Managed
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000Base-T + 2 x Gigabit SFP
Power Over Ethernet (PoE)	PoE+
PoE Budget	120 W
Performance	Switching capacity: 20 Gbps
Remote Management Protocol	SNMP, Syslog, IPv4, IPv6, DHCP
Features	Remote firmware upgrade, DHCP snooping, DHCP relay, 802.1x authentication, ZTP, QoS, non-blocking architecture, cloud managed, fanless
Compliant Standards	IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at
Power	DC 54 V 2.78 A
Dimensions (WxDxH)	22.2 cm x 15 cm x 2.8 cm
Weight	0.88 kg
Manufacturer Warranty	Limited lifetime warranty

Extended Specification

General

Device Type	Switch - 8 ports - Managed
Enclosure Type	Desktop, wall-mountable
Subtype	Gigabit Ethernet
Ports	8 x 10/100/1000Base-T + 2 x Gigabit SFP
Power Over Ethernet (PoE)	PoE+
PoE Budget	120 W
Performance	Switching capacity: 20 Gbps
Remote Management Protocol	SNMP, Syslog, IPv4, IPv6, DHCP
Features	Remote firmware upgrade, DHCP snooping, DHCP relay, 802.1x authentication, ZTP, QoS, non-blocking architecture, cloud managed, fanless
Compliant Standards	IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at
Status Indicators	Power, link/activity, status

Expansion / Connectivity

Interfaces	8 x 1000Base-T RJ-45 PoE+ 2 x 1000Base-X SFP
------------	--

Manufacturer Warranty

Service & Support	Limited warranty - advance hardware replacement - lifetime - response time: next business day Technical support - 1 year
-------------------	--

Power

Power Device	External power adapter
Voltage Required	DC 54 V
Electric Current Required	2.78 A
Power Consumption Stand by	8 Watt

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	45 °C
Humidity Range Operating	5 - 95%
Min Storage Temperature	-20 °C
Max Storage Temperature	70 °C

Dimensions & Weight

Width	22.2 cm
Depth	15 cm
Height	2.8 cm
Weight	0.88 kg

What's in the box

Power Cable