


WD Gold WD181KRYZ (WD181KRYZ)

WD Gold WD181KRYZ - Hard drive - 18 TB - internal - 3.5" - SATA 6Gb/s - 7200 rpm - buffer: 512 MB



The WD Gold is a highly reliable solution for demanding storage environments. Specifically designed for use in enterprise-class storage systems and data centers, the WD Gold Enterprise Class SATA HDD delivers the world-class performance you expect from Western Digital hard drives.

Key Selling Points

- Specifically designed for use in enterprise-class storage systems and datacenters
- Vibration protection technology
- Take on tough workloads; up to 10 times the typical desktop rating
- Enhanced reliability you can trust

Product Features

- Proven reliability
- Enhanced reliability with up to 2.5M hours MTBF.
- High workload
- Take on workloads at up to 10 times the typical desktop rating.
- Vibration protection
- Vibration protection technology gives you peace of mind.

Main specifications

Product Description	WD Gold WD181KRYZ - hard drive - 18 TB - SATA 6Gb/s
Type	Hard drive - internal
Capacity	18 TB
Form Factor	3.5"
Interface	SATA 6Gb/s
Data Transfer Rate	600 MBps
Buffer Size	512 MB
Spindle Speed	7200 rpm
Features	Vibration dampening, HelioSeal, 24x7 continuous operation, advanced format 512e, Energy-Assisted Magnetic Recording (EAMR), Triple State Actuator (TSA)
Dimensions (WxDxH)	101.6 mm x 147 mm x 26.1 mm
Weight	690 g
Localisation	Worldwide
Manufacturer Warranty	5-year warranty

Extended specification

General

Device Type	Hard drive - internal
Capacity	18 TB
Form Factor	3.5"
Interface	SATA 6Gb/s
Buffer Size	512 MB
Features	Vibration dampening, HelioSeal, 24x7 continuous operation, advanced format 512e, Energy-Assisted Magnetic Recording (EAMR), Triple State Actuator (TSA)
Width	101.6 mm

Depth	147 mm
Height	26.1 mm
Weight	690 g

Manufacturer Warranty

Service & Support	Limited warranty - 5 years
-------------------	----------------------------

Miscellaneous

Compliant Standards	RoHS 2011/65/EU
Localisation	Worldwide

Power

Power Consumption	6.5 watt (active) † 5.6 watt (idle)
-------------------	-------------------------------------

Environmental Parameters

Min Operating Temperature	5 °C
Max Operating Temperature	60 °C
Min Storage Temperature	-40 °C
Max Storage Temperature	70 °C
Shock Tolerance (operating)	50 g @ 2 ms half-sine wave
Shock Tolerance (non-operating)	250 g @ 2 ms half-sine wave

Performance

Drive Transfer Rate	600 MBps (external)
Internal Data Rate	269 MBps
Spindle Speed	7200 rpm

Reliability

MTBF	2,500,000 hours
24x7 Operation	Yes

Expansion & Connectivity

Interfaces	1 x SATA 6 Gb/s
Compatible Bay	3.5"

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet