

TP-Link LiteWave LS105G (LS105G)

TP-Link LiteWave LS105G - Switch - unmanaged - 5 x 10/100/1000 - desktop - AC 220 V

The TP-Link LiteWave switches provide easy and affordable way to expand your wired network. They are easy to use and reliable. With these switches, you can expand your network connections to multiple devices instantly.



Key Selling Points

- Durable metal casing
- Traffic prioritization
- Use where you need
- Increase your network speed

Product Features

- Durable metal casing
The interior components of LS105G are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, LS105G delivers switching performance you can depend on.
- Use where you need
The LS105G is fully compatible with networked devices such as computers, printers, webcams, IPTVs. It has a wide range of application scenarios and is suitable for networking in school dormitories, surveillance, homes, and small businesses.

Main specifications

Product Description	TP-Link LiteWave LS105G - switch - 5 ports - unmanaged
Device Type	Switch - 5 ports - unmanaged
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000
Performance	Forwarding performance: 7.4 Mpps
MAC Address Table Size	2K entries
Jumbo Frame Support	16KB
Features	Auto-negotiation, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, store and forward, QoS, fanless, loop prevention
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3x, IEEE 801.1p
Power	AC 220 V (50 Hz)
Dimensions (WxDxH)	9.98 cm x 9.8 cm x 2.5 cm

Extended specification

General

Device Type	Switch - 5 ports - unmanaged
Enclosure Type	Desktop
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000
Performance	Forwarding performance: 7.4 Mpps
MAC Address Table Size	2K entries
Jumbo Frame Support	16KB
Features	Auto-negotiation, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, store and forward, QoS, fanless, loop prevention
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3x, IEEE 801.1p

Status Indicators	Port status, power
-------------------	--------------------

Expansion / Connectivity

Interfaces	5 x 1000Base-T RJ-45
------------	----------------------

Miscellaneous

Compliant Standards	FCC, RoHS
---------------------	-----------

Power

Power Device	External power adapter
Voltage Required	AC 220 V (50 Hz)
Power Consumption Operational	2.776 watt

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-40 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 90% (non-condensing)

Dimensions & Weight

Width	9.98 cm
Depth	9.8 cm
Height	2.5 cm

What's in the box

- TP-Link LiteWave LS105G
- External power adapter

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet