

Cisco (C9400-PWR-3200AC=)

Cisco - Power supply - hot-plug / redundant (plug-in module) - AC 100-240 V - 3200 watt - for P/N: C9404R-48U-BNDL-1A, C9407R-96U-BDL-EDU, C9407R-96U-BNDL-1A, C9407R-96U-BNDL-1E

The Cisco power supply unit is designed to deliver robust and reliable power solutions for network hardware. With hot-plug and redundant features, it ensures that your network remains operational, even in the event of a power supply failure. Offering 3200 W of power and supporting a voltage range of AC 100-240 V, it is equipped to meet the energy demands of a wide array of network devices. Additionally, its integrated Power over Ethernet (PoE) capability allows for the direct powering of devices over network cables, streamlining the setup process and reducing clutter. With an impressive MTBF of 300,000 hours, this power supply is a durable and efficient choice for maintaining network integrity and performance.

Key Selling Points

- Hot-plug and redundant capabilities ensure continuous operation
- 3200 W of power to support demanding network hardware
- AC 100-240 V voltage range for broad compatibility
- Plug-in module form factor for easy integration
- Integrated PoE for efficient device powering

Product Features

- Reliable performance
With an MTBF (Mean Time Between Failures) of 300,000 hours, this power supply promises dependable operation for your network hardware, minimizing downtime and maintenance.
- Efficient power supply
Delivering 3200 W of power, it meets the demanding energy needs of network hardware, ensuring optimal performance. Its compatibility with a wide range of network devices makes it a versatile choice for any setup.
- Integrated PoE support
Features integrated Power over Ethernet (PoE) capabilities, allowing it to power devices directly through network cables. This simplifies installation and reduces the need for additional power sources.

Main specifications

Product Description	Cisco - power supply - hot-plug / redundant - 3200 watt
Device Type	Power supply - hot-plug / redundant - plug-in module
Input Voltage	AC 100-240 V
Power Capacity	3200 watt
Designed For	P/N: C9404R-48U-BNDL-1A, C9407R-96U-BDL-EDU, C9407R-96U-BNDL-1A, C9407R-96U-BNDL-1E, C9407R-96U-BNDL-A

Extended specification

General

Device Type	Power supply - hot-plug / redundant - plug-in module
-------------	--

Miscellaneous

MTBF	300,000 hours
Features	Integrated PoE

Power Device

Input Voltage	AC 100-240 V
Power Capacity	3200 watt

Compatibility Information

Designed For	P/N: C9404R-48U-BNDL-1A, C9407R-96U-BDL-EDU, C9407R-96U-BNDL-1A, C9407R-96U-BNDL-1E, C9407R-96U-BNDL-A
--------------	--