

KATUN[®]
SUCCESS MADE SIMPLE.



PRODUCT SPECIFICATIONS

Arivia C2125, C2130

A3 COLOR MULTIFUNCTION PRINTER

PRODUCT SPECIFICATIONS | Arivia C2125, C2130

BASIC SPECIFICATIONS/COPY FUNCTION

	Arivia C2130	Arivia C2125
Type	Desktop / Console	
Memory capacity	4 GB (Max: 4 GB)	
Storage Device Capacity*1	128 GB	
Color Capability	Full color	
Scan Resolution	600 x 600 dpi	
Printing Resolution	1200 x 2400 dpi (Text-Photo / Photo), 600 x 600 dpi (Text / Map)	
Halftone/Printable Colors	256 levels of Color (16.7 Million Colors)	
Warm-up Time	31 seconds or less (23 degrees Celsius room temperature)	
Recovery Time (Recovery Time from Sleep mode)	15 seconds or less [AC 120V model] 14 seconds or less [AC 220V model] (23 degrees Celsius room temperature)	12 seconds or less (23 degrees Celsius room temperature)
Original Size	Maximum of A3, 11 x 17", 297 x 432 mm for both Sheet and Book	
Paper Size	Max	A3, 11 x 17
	Min	A5 [Postcard (100 x 148 mm), when using Bypass Tray]
Paper Weight	Image loss width*2	Lead edge 4.0 mm, Trail edge 2.0 mm, Right/Left edge 2.0 mm
	Paper Tray	60 to 256 gsm / 16 lb. bond to 142 lb. index
First Copy Output Time	Bypass Tray	60 to 216 gsm / 16 lb. bond to 57 lb. bond
	B/W*3	4.9 sec. (A4 LEF / Letter LEF Monochrome priority mode)
Reduce / Enlarge	Color*4	5.9 sec. (A4 LEF / Letter LEF Monochrome priority mode)
	Color*4	6.7 sec. (A4 LEF / Letter LEF Color priority mode)
Size-to-Size	Color*4	8.1 sec. (A4 LEF / Letter LEF Color priority mode)
	Color*4	1: 1 +/- 0.7%
Continuous Copy Speed*5	Preset	[AC 220V Model]: 50 %, 70 %, 81 %, 94 %, 122 %, 127 %, 141 %, 200 % [AC 120V Model]: 50 %, 70 %, 78 %, 94 %, 129 %, 141 %, 180 %, 200 %
	Variable	25 to 400 % (in 1 % increments)
Paper Tray Capacity*6	A4 LEF / JIS B5 LEF Letter LEF	B/W: 30 ppm, Color: 30ppm
	A4 / JIS B5	B/W: 25 ppm, Color: 25 ppm
	JIS B5	B/W: 23 ppm, Color: 23 ppm
	JIS B4	B/W: 19 ppm, Color: 19 ppm
	Legal	B/W: 17 ppm, Color: 17 ppm
	A3	B/W: 14 ppm, Color: 14 ppm
Standard	520 sheets x 1-tray + Bypass Tray 100 sheets	
Optional	1 Tray Module: 520 sheets x 1-tray 3 Tray Module: 520 sheets x 3-tray Tandem Tray Module: 520 sheets x 1-tray + 870 sheets x 1-Tray + 1180 sheets x 1-Tray High Capacity Feeder B1: 2,000 sheets x 1 Tray	
	Max	2,180 sheets [Standard + 3 Tray Module] 3,190 sheets [Standard + Tandem Tray Module] 5,190 sheets [Standard + Tandem Tray Module + High Capacity Feeder B1]
Continuous Copy *7	999 sheets	
Output Tray Capacity*8	Upper Center: 250 sheets (A4 LEF), Lower Center: 250 sheets (A4 LEF)	
Power Supply	AC 110 - 127 V ±10%, 12 A, 50/60 ±3% Hz common AC 220 - 240 V ±10%, 8A, 50/60 ±3% Hz common	
Maximum Power Consumption	1.45 kW or less (AC110 V ±10%) 1.67 kW or less (AC127 V ±10%) 1.76 kW or less (AC220 V ±10%) 1.92 kW or less (AC240 V ±10%) Sleep Mode : 0.3 W or less : Ready Mode : 101W or less (AC 120V model) Sleep Mode : 0.4 W or less : Ready Mode : 96W or less (AC 220V model)	
Dimensions	W 590 x D 659 x H 768 mm / W 23.3 x D 26.0 x H 30.3" W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional 1 Tray Module with Cabinet Module is installed.) W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional 3 Tray Module is installed.) W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional Tandem Tray Module is installed.)	
Weight*9	70 kg / 155lb. 93 kg / 205lb. (When optional 1 Tray Module with Cabinet is installed.) 96 kg / 212lb. (When optional 3 Tray Module is installed.) 100 kg / 221lb. (When optional Tandem Tray Module is installed.)	
Space Requirement*10	W 971 x D 659 mm / W38.3 x 26.0" (when the Bypass Tray is fully extended)	

*1: The Storage Device Capacity is not totally available for customers.

*2: It may change depending on usage conditions.

*3: It is recommended to use our recommended paper. Correct print output may not be possible depending on the requirement.

*4: The speed may be reduced due to the image quality adjustment.

*5: 20 lb./75 gsm paper.

*6: Copy process may stop temporarily for stabilization of image quality.

*7: 70 gsm paper.

*8: Including Toner Cartridge.

PRINT FUNCTION

Type	Built-in type	
Continuous Print Speed*3	Same as the Basic Specifications / Copy Function	
Printing Resolution Standard	[PCL Driver] Standard: 1200 x 2400 dpi, High Quality: 1200 x 2400 dpi, High Resolution*2: 1200 x 1200 dpi	
	[Adobe® PostScript® 3TM Driver] High Speed (Standard): 600 x 600 dpi, High Quality: 1200 x 2400 dpi, High Resolution*2: 1200 x 1200 dpi	
Page Description Language Standard	PCL5 / PCL6	
Network Protocol (Standard)	Adobe® PostScript® 3TM	
Ethernet (Standard)	TCP/IP (Ipd, IPP, Port9100, WSD)	
Supported Operating System*4	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit)	
	[Mac OS X Driver] MacOS 14 / 13 / 12 / 11	
Fonts Standard	[Adobe® PostScript® 3TM Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit), Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) MacOS 14 / 13 / 12 / 11	
	PCL : 85 fonts	
Emulation Standard	Adobe® PostScript® 3TM Kit:136 European fonts	
Interface Standard	PDF, XPS, TIFF, JPEG, Adobe® PostScript® 3TM, PCL5 / PCL6, HP-GL2	
Optional	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB3.0	
	Wireless LAN (IEEE 802.11 a / b / g / n / ac)	

Note: WSD stands for Web Services on Devices.

Note: XPS stands for XML Paper Specification.

*1: Long paper of 106 to 220 gsm (Extra Heavyweight) is available. The printed papers are delivered to the Side Tray when Finisher-A2 / Finisher-C4 / Finisher-C4 with Booklet Maker is attached.

*2: Up to A3 size.

*3: The speed may be reduced due to the image quality adjustment. The printing speed may be reduced depending on the document.

*4: Please refer to our official website for the latest supported OS.

*5: High Resolution mode is recommended for printing fine lines or cadastral maps

SCAN FUNCTION

Type	Color Scanner	
Original Size	Same as the Basic Specifications / Copy Function	
Scan Resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi	
Scan Speed	Same as the Scan Speed for the Duplex Automatic Document Feeder	
Interface	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T
	Optional	Wireless LAN (IEEE 802.11 a / b / g / n / ac)
Network Protocol	TCP/IP (WebDAV, HTTP)	
	File Format	Monochrome binary: TIFF, PDF*1 Grayscale: TIFF, JPEG*2, PDF*3 Full Color: TIFF, JPEG, PDF*1, Highly compressed PDF*1
Scan to Folder	Driver	TWAIN Interface support
	Operating System*3	Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit)
Network Protocol	TCP/IP (SMB, FTP, SFTP)	
	Operating System	Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) MacOS 14*4 / 13*4 / 12*4 / 11*4
Scan to PC	File Format	Monochrome binary: TIFF, PDF Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF
	Network Protocol	TCP/IP (SMTP)
Scan to e-mail	File Format	Monochrome binary: TIFF, PDF Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF

*1: When Internet Services is used.

*2: When Network Scanner Utility 3 is used.

*3: Please refer our official website for the latest supported OS.

*4: Only SMB is supported.

FAX FUNCTION (OPTIONAL)

Original Size	Max: A3, 11 x 17", Long document (Longest 600 mm / 23.7")
Recording Paper Size	Max: A3, 11 x 17"; Min: A5
Transmission Time	2 seconds and more but fewer than 3 seconds*
Transmission Mode	ITU-T G3
Standard	8 x 3.85 line/mm, 200 x 100 dpi
Fine	8 x 7.7 line/mm, 200 x 200 dpi
Scanning Resolution (400dpi)	16 x 15.4 line/mm, 400 x 400 dpi
Super Fine (600dpi)	600 x 600 dpi
Coding Method	MH, MR, MMR, JBIG
Transmission Speed	G3: 33.6 / 31.2 / 28.8 / 26.4 / 24.0 / 21.6 / 19.2 / 16.8 / 14.4 / 12.0 / 9.6 / 7.2 / 4.8 / 2.4 kbps
Applicable Lines	Telephone subscriber line, PBX, Fax communication (PSTN)

* When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 3.85 lines/mm) and in high-speed mode (28.8 kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition.

DIRECT FAX FUNCTION (OPTIONAL)

Original Size	A3, JIS B4, A4
Resolution	As same image quality indicated in Scanning Resolution for Fax Function
Transmission Speed	Same as the Fax Function
Applicable Lines	Same as the Fax Function
Supported Operating System*	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) [Mac OS X Driver] MacOS 14 / 13 / 12 / 11

*: Please refer to our official website for the latest supported OS.

INTERNET FAX FUNCTION (OPTIONAL)

Original Size	A3, JIS B4, A4
Scanning Resolution	Same as the Fax Function
File Format	Format: TIFF-FB; Compression method: MH, MMR, JBIG
Profile	TIFF-S, TIFF-F, TIFF-J
Network Protocol	Transmission SMTP Reception SMTP, POP3
Interface Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T

DUPLEX FUNCTION

Paper Size	Same as the Basic Specifications / Copy Function
Paper Weight	60 to 169 gsm / 16 lb. bond to 45 lb. bond

DUPLEX AUTOMATIC DOCUMENT FEEDER C2-PC [1 PASS, 2 SIDED SCANNING]

Type	1 pass, 2 sided scanning Duplex Automatic Document Feeder
Original Size / Paper Weight	Max: A3, 11 x 17"; Min: A6*1 38 to 128 gsm / 11 lb. bond to 34 lb. bond (In Duplex: 50 to 128 gsm / 14 lb. bond to 34 lb. bond) *2
Capacity*3	130 sheets
Scan Speed*3	Copy (A4 LEF, Simplex) B/W: 25 ppm Color: 25 ppm Scan B/W: 80 ppm, Color: 80 ppm (1 pass, 2 sided scanning: B/W 80 ppm, Color 80 ppm) [Standard Paper (A4 LEF / Letter LEF), 200 dpi, to Folder.]

*1: The minimum custom size is 49 x 85 mm / 2.0 x 3.4".

*2: Custom sizes from 49 x 85 mm to 55 x 91 mm are available from 38 to 209 gsm.

*3: 70 gsm paper.

*4: The scanning speed varies depending on the documents.

HIGH CAPACITY FEEDER B1 (OPTIONAL)

Paper Size	A4 LEF, Letter LEF, JIS B5 LEF
Paper Weight	55 to 216 gsm / 15 lb. bond to 57 lb. bond
Feeding Capacity / Number of Tray*1	2000 sheets x 1-tray
Dimensions	W 389 x D 610 x H 377 mm / W 15.4 x D 24.1 x H 14.9"
Weight	29 kg / 64 lb.
Space Requirement*2	W 1056 x D 720 mm / W 41.6 x D 28.4"

*1: 80 gsm paper.

*2: Main Unit + High Capacity Feeder B1 ; When the Bypass Tray are fully extended.

Finisher-A2 (OPTIONAL)

Type	Sort (Offset available) / Stack (Offset available) Default: No Offset
Paper Size	Max: A3, 11 x 17"; Min: Postcard (100 x 148 mm)
Paper Weight	60 to 256 gsm / 16 lb. bond to 142 lb. index
Paper Capacity*1	[Without Stapling] A4: 500 sheets; JIS B4: 250 sheets; A3 or larger: 200 sheets; Mixed Size Stacking*2: 250 sheets [With Stapling] 30 sets
Staple	Capacity: Paper Size A4: 50 sheets (90 gsm or less), JIS B4 or larger: 30 sheets (90 gsm or less); Paper Size: Max: A3, 11 x 17"; Min: JIS B5 LEF Paper Weight: 60 to 256 gsm / 16 lb. bond to 142 lb. index Position: Single stapling, Dual stapling
Dimensions*3 / Weight	W 658 x D 461 x H 238 mm / W 25.9 x D 18.2 x H 9.4" 11 kg / 25lb.
Space Requirement (When connected to the main unit) *4	W 1132 x D 659 mm / W 44.6 x 26.0"

*1: 70 gsm paper.

*2: When larger size sheets are stacked on top of smaller size sheets.

*3: Width 478 mm when the paper support is stored.

*4: Main Unit + Finisher-A2; when the paper support is pulled out and the Bypass Tray is fully extended.

FINISHER-B4 (OPTIONAL)

Type	Sort (Offset available*1*2) / Stack (Offset available*1*2)
Paper Size*3	Max: A3, 11 x 17"; Min: A5
Paper Weight*4	60 to 256 gsm / 16 lb. bond to 142 lb. index
Paper Capacity*5	[Without Stapling] A4: 2000 sheets, JIS B4 or larger: 1000 sheets, Mixed Size Stacking*5: 300 sheets [With Stapling] A4: 100 sets or 1000 sheets*6, JIS B4 or larger: 75 sets or 750 sheets [With Booklet Finishing*7] 50 sets or 600 sheets [With Fold*7] 500 sheets
Staple	Capacity A4: 50 sheets (90 gsm or less)
	Paper Size*10 Max: A3, 11 x 17"; Min: A5 LEF
	Paper Weight 60 to 256 gsm / 14 lb. bond to 142 lb. index
	Position Single stapling, Dual stapling
Punch*11	Number of Holes 2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications)
	Paper Size*12 Max: A3, 11 x 17"; Min: A5 LEF
	Paper Weight 60 to 220 gsm / 16 lb. bond to 122 lb. index
Booklet Finishing*8	Capacity Saddle Staple: 15 sheets; Single Fold: 5 sheets
	Paper Size Max: A3, 11 x 17"; Min: A4, Letter
	Paper Weight Saddle Staple: 60 to 80 gsm / 16 lb. bond to 21 lb. bond*11 Single Fold: 60 to 105 gsm / 16 lb. bond to 28 lb. bond
Dimensions*14	W 607 x D 653 x H 1041 mm / W 23.9 x D 25.7 x H 41.0" With Booklet Finisher: W 607 x D 673 x H 1079 mm / W 23.9 x D 26.5 x H 42.5"
Weight *15	26 kg / 58 lb. Punch Kit: + 2 kg / 5 lb. Booklet Maker Unit: + 10 kg / 22 lb.
Space Requirement (When connected to the main unit) *16	W 1519 x D 659 mm / W 59.8 x D 26.0" With Booklet Finisher: W 1519 x D 673 mm / W 59.8 x D 26.5"

Installation Kit Required.

Note: Finisher-B4 is available only when optional 1 Tray Module or 3 Tray Module or Tandem Tray Module is attached to Main Unit.

*1: The offset feature is set to disabled by factory default. The setting can be changed as necessary.

*2: Outputs less than 210 mm width are delivered without offset stacking.

*3: Paper in the sizes larger than A3 or 11 x 17" or smaller than A5 are delivered to the Centre Tray.

*4: 70 gsm paper.

*5: When larger size sheets are stacked on top of smaller size sheets.

*6: 75 sets or 750 sheets with dual stapling.

*7: The Booklet Finishing function requires the optional Booklet Maker Unit for Finisher-B. Make a crease

allows you to fold easily. After a job with the Booklet Finishing function specified has been output, the

next job may not be delivered until the sheets are removed from the output tray. Also, if larger size

sheets are stacked on top of smaller size sheets after a job with the Booklet Finishing function specified

has been run, the next job may not be delivered until the sheets are removed from the output tray.

*8: Available staple positions vary depending on the paper size.

*9: The Punch function requires the optional 2/4 Hole Punch Kit for Finisher-B or US 2/3 Hole Punch Kit for Finisher-B.

*10: Available number of punch holes varies depending on the paper size.

*11: Covers can be up to 220 gsm (Extra Heavyweight).

*12: Inner connector within the body is excluded.

*13: Main Unit + Finisher-B4; When the paper support is pulled out and the Bypass Tray is fully extended.

Arivia C2125, C2130

COLOR A3 MULTIFUNCTION PRINTER

Katun's portfolio of Arivia color MFP's for large workgroups feature state-of-the-art technology that makes it easy to run your business and maximize productivity. Designed to integrate into any office environment, Arivia MFP's are designed to withstand today's security threats, offer an intuitive user experience, and deliver enhanced workflow solutions. Smartly designed for reliability and to minimize service calls, and with print speeds up to 65ppm, scan speeds up to 270ppm and a full range of input and finishing options, Arivia is powerful asset to your business.



For complete information on Katun products, please visit: www.katun.com

© 2024 Katun. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

KATUN®

7760 France Ave. So. Suite 340
Minneapolis, MN 55435
1-800-328-2965 | katun.com

