

**KATUN**<sup>®</sup>  
SUCCESS MADE SIMPLE.



PRODUCT SPECIFICATIONS

Arivia C3135, C3145,  
C4155, C4165

A3 COLOR MULTIFUNCTION PRINTER

PRODUCT SPECIFICATIONS | Arivia C3135, C3145, C4155, C4165

BASIC SPECIFICATIONS/COPY FUNCTION

	Arivia C4165	Arivia C4155	Arivia C3145	Arivia C3135	
Type	Console				
Memory capacity	4 GB (Max: 4 GB)				
Storage Device Capacity <sup>*1</sup>	128 GB				
Color Capability	Full color				
Scan Resolution	600 x 600 dpi				
Printing Resolution	1200 x 2400 dpi (Text-Photo / Photo), 600 x 600 dpi (Text / Map)				
Halftone/Printable Colors	256 levels of Color (16.7 Million Colors)				
Warm-up Time	30 seconds or less (23 degrees Celsius room temperature)				
Recovery Time (Recovery Time from Sleep mode)	13 seconds or less (23 degrees Celsius room temperature)	11 seconds or less (23 degrees Celsius room temperature)	5 seconds or less (23 degrees Celsius room temperature)		
Original Size	Maximum of A3, 11 x 17", 297 x 432 mm for both Sheet and Book				
Paper Size	Max	SRA3 (320 x 450 mm), 12 x 18" (305 x 457 mm), A3 [12 x 19" (305 x 483 mm), 320 x 483 mm / 12.6 x 19.1" when using Bypass Tray]			
	Min	A5, Postcard (100 x 148 mm) [89 x 98 mm / 3.5 x 3.9" when using Bypass Tray]			
	Image loss width <sup>*2</sup>	Lead edge 4.0 mm, Trail edge 2.0 mm, Right/Left edge 2.0 mm			
Paper Weight	Paper Tray	52 to 300 gsm / 14 lb. bond to 111 lb. cover			
	Bypass Tray	52 to 300 gsm / 14 lb. bond to 111 lb. cover			
First Copy Output Time	B/W <sup>*3</sup>	3.3 sec.	3.7 sec.	4.4 sec.	
	Color <sup>*4</sup>	4.1 sec.	5.2 sec.	5.7 sec.	
Size-to-Size	1:1 +/- 0.7 %				
Reduce / Enlarge	Preset	[AC 220V Model]: 50 %, 70 %, 81 %, 94 %, 122 %, 127 %, 141 %, 200 % [AC 120V Model]: 50 %, 70 %, 78 %, 94 %, 129 %, 141 %, 180 %, 200 %			
	Variable	25 to 400 % (in 1 % increments)			
	A4 LEF/ JIS B5 LEF	B/W: 65 ppm Color: 65 ppm	B/W: 55 ppm Color: 55 ppm	B/W: 45 ppm Color: 45 ppm	B/W: 35 ppm Color: 35 ppm
Continuous Copy Speed <sup>*5</sup>	Letter LEF	B/W: 65 ppm Color: 65 ppm	B/W: 55 ppm Color: 55 ppm	B/W: 45 ppm Color: 45 ppm	B/W: 35 ppm Color: 35 ppm
	A4 / JIS B5	B/W: 47 ppm Color: 47 ppm	B/W: 40 ppm Color: 40 ppm	B/W: 32 ppm Color: 32 ppm	B/W: 27 ppm Color: 27 ppm
	JIS B4	B/W: 38 ppm Color: 38 ppm	B/W: 32 ppm Color: 32 ppm	B/W: 26 ppm Color: 26 ppm	B/W: 23 ppm Color: 23 ppm
	Legal	B/W: 38 ppm Color: 38 ppm	B/W: 32 ppm Color: 32 ppm	B/W: 26 ppm Color: 26 ppm	B/W: 22.5 ppm Color: 22.5 ppm
	A3	B/W: 32 ppm Color: 32 ppm	B/W: 27 ppm Color: 27 ppm	B/W: 22 ppm Color: 22 ppm	B/W: 19 ppm Color: 19 ppm
Paper Tray Capacity <sup>*6</sup>	Standard	4 Tray Model: 520 sheets x 4-tray + Bypass Tray 90 sheets Tandem Tray Model: 520 sheets x 2-tray + 840 sheets + 1230 sheets + Bypass Tray 90 sheets			
	Optional	High Capacity Feeder B1: 2000 Sheets High Capacity Feeder B2: 2940 sheets			
	Max	Tandem Tray Model: 6,140 sheets (Tandem Tray Model + High Capacity Feeder B2)   4 Tray Model: 5,110 sheets (4 Tray Model + High Capacity Feeder B2)			
Continuous Copy <sup>*7</sup>	999 sheets				
Output Tray Capacity <sup>*8</sup>	Upper Center: 250 sheets (A4 LEF), Lower Center: 250 sheets (A4 LEF)				
Power Supply	AC110-127V +/-10%, 12A+7A, 50/60Hz common (2Power) [C4165] AC110-127V +/-10%, 12A, 50/60Hz common [C4155/C3145/C3135] AC220-240V +/-10%, 10A, 50/60Hz common				
	Maximum Power Consumption	1.936 kW (AC110V) 2.235 kW (AC127V) 2.2 kW (AC220V) 2.4 kW (AC240V) Sleep mode:0.5W (AC115V) Ready mode:92W (AC115V) Sleep mode:0.5W (AC230V) Ready mode:110W (AC230V)			
Dimensions	C4165: W 658 x D 790 x H 1169 / W 25.9 x D 31.1 x H 46.1" C4155: W 658 x D 790 x H 1169 mm / W 25.9 x D 31.1 x H 46.1" C3145: W 658 x D 790 x H 1169 mm / W 25.9 x D 31.1 x H 46.1" C3135: W 633 x D 677 x H 1119 mm / W 25.0 x D 26.7 x H 44.1"				
Weight <sup>*9</sup>	156 kg / 344 lb.		146 kg / 322 lb.   124 kg / 274 lb.		
Space Requirement <sup>*10</sup>	C4165: W 1134 x D 790 mm / W 44.7 x D 31.1" C4155/C3145: W 1134 x D 790 mm / W 44.7 x D 31.1" C3135: W 1032 x D 677 mm / W 40.7 x D 26.7"				

\*1: The Storage Device Capacity is not totally available for customers.  
 \*2: Up to A3 size.  
 \*3: A4 LEF or Letter LEF / Monochrome priority mode.  
 \*4: A4 LEF or Letter LEF / Color priority mode.  
 \*5: The speed may be reduced due to the image quality adjustment.  
 \*6: 80 gsm paper.  
 \*7: Copy process may stop temporarily for stabilization of image quality  
 \*8: 70 gsm paper.  
 \*9: Excluding Toner Cartridge.  
 \*10: When the Bypass Tray is fully extended and the stopper of DADF is turned on

PRINT FUNCTION

Type	Built-in type			
Print Size	Max	SRA3 (320 x 450 mm), 12 x 18" (305 x 457 mm), A3 [12 x 19" (305 x 483 mm), 320 x 1200 mm <sup>*1</sup> / 12.6 x 47.3" when using Bypass Tray]		
	Min	A5, Postcard (100 x 148 mm) [89 x 98 mm / 3.5 x 3.9" when using Bypass Tray]		
	Image loss width <sup>*2</sup>	Lead edge 4.0 mm, Trail edge 2.0 mm, Right/Left edge 2.0 mm		
Continuous Print Speed <sup>*3</sup>	Same as the Basic Specifications / Copy Function			
Printing Resolution	Standard	[PCL Driver] Standard: 1200 x 2400 dpi, High Quality: 1200 x 2400 dpi, High Resolution <sup>*5</sup> : 1200 x 1200 dpi		
	Standard	[Adobe® PostScript® 3TM Driver] High Speed (Standard): 600 x 600 dpi, High Quality: 1200 x 2400 dpi, High Resolution <sup>*5</sup> : 1200 x 1200 dpi		
Page Description Language	PCL5 / PCL6			
Network Protocol (Standard)	Ethernet (Standard)	TCP/IP (Ipd, IPP, Port9100, WSD)		
Supported Operating System <sup>*4</sup>	Standard	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit)		
	Standard	[Mac OS X Driver] MacOS 14 / 13 / 12 / 11		
	Standard	[Adobe® PostScript® 3TM Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit), Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) MacOS 14 / 13 / 12 / 11		
Fonts	Standard	PCL : 85 fonts Adobe® PostScript® 3TM Kit:136 European fonts		
Emulation	Standard	PDF, XPS, TIFF, JPEG, Adobe® PostScript® 3TM, PCL5 / PCL6, HP-GL2		
Interface	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB3.0		
	Optional	Wireless LAN (IEEE 802.11 a / b / g / n / ac)		
Note: WSD stands for Web Services on Devices. Note: XPS stands for XML Paper Specification. *1: Long paper of 106 to 220 gsm (Extra Heavyweight) is available. The printed papers are delivered to the Side Tray when Finisher-A2 / Finisher-C4 / Finisher-C4 with Booklet Maker is attached. *2: Up to A3 size. *3: The speed may be reduced due to the image quality adjustment. The printing speed may be reduced depending on the document. *4: Please refer to our official website for the latest supported OS. *5: High Resolution mode is recommended for printing fine lines or cadastral maps				
SCAN FUNCTION				
Type	Color Scanner			
Original Size	Same as the Basic Specifications / Copy Function			
Scan Resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi			
Scan Speed	Same as the Scan Speed for the Duplex Automatic Document Feeder			
Interface	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T		
	Optional	Wireless LAN (IEEE 802.11 a / b / g / n / ac)		
Network Protocol	Standard	TCP/IP (WebDAV, HTTP)		
	Optional	TCP/IP (WebDAV, HTTP)		
Scan to Folder	File Format	Monochrome binary: TIFF, PDF <sup>*1</sup> Grayscale: TIFF, JPEG <sup>*2</sup> , PDF <sup>*1</sup> Full Color: TIFF, JPEG, PDF <sup>*1</sup> , Highly compressed PDF <sup>*1</sup>		
	Driver	TWAIN Interface support		
Operating System <sup>*3</sup>	Standard	Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit)		
	Standard	TCP/IP (SMB, FTP, SFTP)		
Scan to PC	Operating System	Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) MacOS 14 <sup>*4</sup> / 13 <sup>*4</sup> / 12 <sup>*4</sup> / 11 <sup>*4</sup>		
	File Format	Monochrome binary: TIFF, PDF Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF		
Scan to e-mail	Network Protocol	TCP/IP (SMTP)		
	File Format	Monochrome binary: TIFF, PDF Grayscale/Full Color: TIFF, JPEG, PDF, Highly compressed PDF		

\*1: When Internet Services is used.  
 \*2: When Network Scanner Utility 3 is used.  
 \*3: Please refer our official website for the latest supported OS.  
 \*4: Only SMB is supported.

## FAX FUNCTION (OPTIONAL)

<b>Original Size</b>	Max: A3, 11 x 17", Long document (Longest 600 mm / 23.7")
<b>Recording Paper Size</b>	Max: A3, 11 x 17"; Min: A5
<b>Transmission Time</b>	2 seconds and more but fewer than 3 seconds*
<b>Transmission Mode</b>	ITU-T G3
<b>Standard</b>	8 x 3.85 line/mm, 200 x 100 dpi
<b>Fine</b>	8 x 7.7 line/mm, 200 x 200 dpi
<b>Scanning Resolution (400dpi)</b>	16 x 15.4 line/mm, 400 x 400 dpi
<b>Super Fine (600dpi)</b>	600 x 600 dpi
<b>Coding Method</b>	MH, MR, MMR, JBIG
<b>Transmission Speed</b>	G3: 33.6 / 31.2 / 28.8 / 26.4 / 24.0 / 21.6 / 19.2 / 16.8 / 14.4 / 12.0 / 9.6 / 7.2 / 4.8 / 2.4 kbps
<b>Applicable Lines</b>	Telephone subscriber line, PBX, Fax communication (PSTN)

\* When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 3.85 lines/mm) and in high-speed mode (28.8 kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition.

## DIRECT FAX FUNCTION (OPTIONAL)

<b>Original Size</b>	A3, JIS B4, A4
<b>Resolution</b>	As same image quality indicated in Scanning Resolution for Fax Function
<b>Transmission Speed</b>	Same as the Fax Function
<b>Applicable Lines</b>	Same as the Fax Function
<b>Supported Operating System*</b>	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit) Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) [Mac OS X Driver] MacOS 14 / 13 / 12 / 11

\*: Please refer to our official website for the latest supported OS.

## INTERNET FAX FUNCTION (OPTIONAL)

<b>Original Size</b>	A3, JIS B4, A4
<b>Scanning Resolution</b>	Same as the Fax Function
<b>File Format</b>	Format: TIFF-FB; Compression method: MH, MMR, JBIG
<b>Profile</b>	TIFF-S, TIFF-F, TIFF-J
<b>Network Protocol</b>	<b>Transmission</b> SMTP <b>Reception</b> SMTP, POP3
<b>Interface Standard</b>	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T

## DUPLEX FUNCTION

<b>Paper Size</b>	Max: SRA3 (320 x 450 mm), 12 x 18" (305 x 457 mm), A3; Min: A5
<b>Paper Weight</b>	52 to 300 gsm / 14 lb. bond to 111 lb. cover

## DUPLEX AUTOMATIC DOCUMENT FEEDER B2-PC [1 PASS, 2 SIDED SCANNING] Arivia C3135

<b>Type</b>	1 pass, 2 sided scanning Duplex Automatic Document Feeder
<b>Original Size / Paper Weight</b>	Max: A3, 11 x 17"; Min: A6* <sup>1</sup> 38 to 128 gsm / 11 lb. bond to 34 lb. bond (In Duplex: 50 to 128 gsm / 14 lb. bond to 53 lb. bond)* <sup>2</sup>
<b>Capacity</b> <sup>*3</sup>	130 sheets
<b>Scan Speed</b> <sup>*4</sup>	<b>Copy (A4 LEF, Simplex)</b> B/W: 35 ppm Color: 35 ppm <b>Scan</b> B/W: 80 ppm, Color: 80 ppm (1 pass, 2 sided scanning; B/W 160 ppm, Color 160 ppm) [Standard Document (A4 LEF/Letter LEF), 200 dpi, to Folder.]

\*1: The minimum custom size is 49 x 85 mm / 2.0 x 3.4".

\*2: Custom sizes from 49 x 85 mm to 55 x 91 mm are available from 38 to 209 gsm.

\*3: 70 gsm paper.

\*4: The scanning speed varies depending on the documents.

## DUPLEX AUTOMATIC DOCUMENT FEEDER C2-PC [1 PASS, 2 SIDED SCANNING]

	Arivia C4165	Arivia C4155	Arivia C3145
<b>Type</b>	1 pass, 2 sided scanning Duplex Automatic Document Feeder		
<b>Original Size / Paper Weight</b>	Max: A3, 11 x 17"; Min: A6* <sup>1</sup> 38 to 200 gsm / 11 lb. bond to 53 lb. bond (In Duplex: 50 to 200 gsm / 14 lb. bond to 53 lb. bond)* <sup>2</sup>		
<b>Capacity</b> <sup>*3</sup>	250 sheets		
<b>Scan Speed</b> <sup>*4</sup>	<b>Copy (A4 LEF, Simplex)</b> B/W: 65 ppm Color: 65 ppm	B/W: 55 ppm Color: 55 ppm	B/W: 45 ppm Color: 45 ppm
<b>Scan</b>	B/W: 135 ppm, Color: 135 ppm (1 pass, 2 sided scanning: B/W 270 ppm, Color 270 ppm) [Standard Document (A4 LEF/Letter LEF), 200 dpi, to Folder.]		

\*1: The minimum custom size is 84 x 139.7 mm / 3.3 x 5.5".

\*2: 70 gsm paper.

\*3: The scanning speed varies depending on the documents.

## HIGH CAPACITY FEEDER B1 (OPTIONAL)

<b>Paper Size</b>	A4 LEF, Letter LEF, JIS B5 LEF
<b>Paper Weight</b>	55 to 216 gsm / 15 lb. bond to 57 lb. bond
<b>Feeding Capacity / Number of Tray</b> <sup>*1</sup>	2000 sheets x 1-tray
<b>Dimensions</b>	W 389 x D 610 x H 377 mm / W 15.4 x D 24.1 x H 14.9"
<b>Weight</b>	29 kg / 64 lb.
<b>Space Requirement</b> <sup>*2</sup>	[C4165] : W 1134 x D 790 mm / W 44.7 x D 31.1" [C4155 / C3145] : W 1134 x D 790 mm / W 44.7 x D 31.1" [C3135] : W 1032 x D 677 mm / W 40.7 x D 26.7"

\*1: 80 gsm paper.

\*2: Main Unit + High Capacity Feeder B1 ; When the Bypass Tray are fully extended.

## HIGH CAPACITY FEEDER B2 (OPTIONAL)

<b>Paper Size</b>	A4 LEF, Letter LEF, JIS B5 LEF
<b>Paper Weight</b>	55 to 216 gsm
<b>Feeding Capacity / Number of Tray</b> <sup>*1</sup>	2940 sheets x 1-tray
<b>Dimensions</b>	W 476 x D 618 x H 433 mm
<b>Weight</b>	31 kg
<b>Space Requirement</b> <sup>*2</sup>	[C4165] : W 1181 x D 790 mm [C4155 / C3145] : W 1181 x D 790 mm [C3135] : W 1079 x D 677 mm

\*1: 80 gsm paper.

\*2: Main Unit + High Capacity Feeder B2; When the Extension Tray / Bypass Tray are fully extended.

## SIDE TRAY

<b>Paper Size</b>	Same as the Basic Specifications / Copy Function
<b>Paper Weight</b>	52 to 300 gsm / 14 lb. bond to 111 lb. cover
<b>Paper Capacity</b> <sup>*1</sup>	100 sheets
<b>Dimensions</b>	W 327 x D 414 x H 179 mm / W 12.9 x D 16.3 x H 7.1"
<b>Space Requirement (When connected to the main unit)</b> <sup>*2</sup>	[C4165] : W 1134 x D 790 mm / W 44.7 x D 31.1" [C4155 / C3145] : W 1134 x D 790 mm / W 44.7 x D 31.1" [C3135] : W 1032 x D 677 mm / W 40.7 x D 26.7"

\*1: 70 gsm paper.

\*2: Main Unit + Side Tray; When the Bypass Tray is fully extended and the stopper of DADF is turned on

## PRODUCT SPECIFICATIONS | Arivia C3135, C3145, C4155, C4165

### FINISHER-A2 (OPTIONAL)

<b>Type</b>	Sort (Offset available*) / Stack (Offset available***)
<b>Paper Size</b>	Max: A3, 11 x 17"; Min: A5, Postcard (100 x 148 mm)
<b>Paper Weight**2</b>	52 to 256 gsm
<b>Paper Capacity**3</b>	[Without Stapling] A4 LEF: 500 sheets, JIS B4: 250 sheets, A3 or larger: 200 sheets, Mixed Size Stacking**4: 250 sheets [With Stapling] 30 sets, or A4 LEF: 500 sheets, JIS B4: 250 sheets, A3 or larger: 200 sheets, Mixed Size Stacking**4: 250 sheets
<b>Staple</b>	<b>Capacity</b> A4: 50 sheets (90 gsm or less), JIS B4 or larger: 30 sheets (90 gsm or less) <b>Paper Size</b> Max: A3, 11 x 17"; Min: JIS B5 LEF <b>Paper Weight</b> 52 to 256 gsm <b>Position</b> Single stapling, Dual stapling
<b>Dimensions / Weight</b>	W 478 x D 461 x H 238 mm, 11 kg
<b>Space Requirement (When connected to the main unit) **5</b>	[C4155 / C3145]: W 1263 x D 790 mm [C3135]: W 1263 x D 677 mm

Note: The unit cannot be installed on C4165.

\*1: [No Offset] is selected by factory default. The settings can be changed according to the customer's use situation.

\*\*2: Documents may not be printed correctly depending on usage conditions. (52 to 55 gsm)

\*\*3: 70 gsm paper.

\*\*4: When larger size sheets are stacked on top of smaller size sheets: 250 sheets (when large size sheets are smaller than A3) / 200 sheets (when large size sheets are A3 or larger)  
The same applies to when staple-free and stapled bindings are mixed or different stapling positions are mixed.

\*\*5: Main Unit + Finisher-A2; when the paper support is pulled out and the Bypass Tray is fully extended.

### FINISHER- B4 (OPTIONAL)

<b>Type</b>	Sort (Offset available**2) / Stack (Offset available**2)
<b>Paper Size**3</b>	Max: A3, 11 x 17"; Min: A5
<b>Paper Weight**4</b>	52 to 300 gsm / 14 lb. bond to 111 lb. cover
<b>Paper Capacity**5</b>	[Without Stapling] A4: 2000 sheets, JIS B4 or larger: 1000 sheets, Mixed Size Stacking**6: 300 sheets [With Stapling] A4: 100 sets or 1000 sheets**7, JIS B4 or larger: 75 sets or 750 sheets [With Booklet Finishing**8] 50 sets or 600 sheets [With Fold**9] 500 sheets
<b>Staple</b>	<b>Capacity</b> 50 sheets (90 gsm or less) <b>Paper Size**9</b> Max: A3, 11 x 17"; Min: A5 LEF <b>Paper Weight</b> 52 to 256 gsm / 14 lb. bond to 142 lb. index <b>Position</b> Single stapling, Dual stapling
<b>Punch**10</b>	<b>Number of Holes</b> 2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications) <b>Paper Size**11</b> Max: A3, 11 x 17"; Min: A5 LEF <b>Paper Weight</b> 52 to 220 gsm / 14 lb. bond to 122 lb. index <b>Capacity</b> Saddle Staple: 15 sheets; Single Fold: 5 sheets
<b>Booklet Finishing**8</b>	<b>Paper Size</b> Max: A3, 11 x 17"; Min: A4, Letter <b>Paper Weight</b> Saddle Staple: 64 to 80 gsm / 18 lb. bond to 21 lb. bond**12 Single Fold: 64 to 105 gsm / 18 lb. bond to 28 lb. bond
<b>Dimensions**13</b>	W 592 x D 653 x H 1041 mm / W 23.3 x D 25.7 x H 41.0" With Booklet Maker Unit: W 592 x D 673 x H 1076 mm / W 23.3 x D 26.5 x H 42.4"
<b>Weight**14</b>	26 kg / 58 lb. Punch Kit: + 2 kg / 5 lb. Booklet Maker Unit: + 10 kg / 22 lb.
<b>Space Requirement**15</b>	[C4165]: W 1642 x D 790 mm / W 64.7 x D 31.1" With Booklet Maker Unit: W 1642 x D 790 mm / W 64.7 x D 31.1" [C4155 / C3145]: W 1642 x D 790 mm / W 64.7 x D 31.1" With Booklet Maker Unit: W 1642 x D 790 mm / W 64.7 x D 31.1" [C3135]: W 1642 x D 678 mm / W 64.7 x D 26.7" With Booklet Maker Unit: W 1642 x D 678 mm / W 64.7 x D 26.7"

Installation Kit required for use with Arivia C3135.

\*1: The offset feature is set to disabled by factory default. The setting can be changed as necessary.

\*\*2: Outputs whose weight is 257 gsm and more or width is less than 210 mm are delivered without offset stacking.

\*\*3: Paper in the sizes larger than A3 or 11 x 17" or smaller than A5 are delivered to the Centre Tray.

\*\*4: Documents may not be printed correctly depending on usage conditions. (52 to 55 gsm, 257 gsm and more)

\*\*5: 70 gsm paper.

\*\*6: When larger size sheets are stacked on top of smaller size sheets.

\*\*7: 75 sets or 750 sheets with dual stapling.

\*\*8: The Booklet Finishing function requires the optional Booklet Maker Unit for Finisher-B. Make a crease allows you to fold easily. After a job with the Booklet Finishing function specified has been output, the next job may not be delivered until the sheets are removed from the output tray. Also, if larger size sheets are stacked on top of smaller size sheets after a job with the Booklet Finishing function specified has been run, the next job may not be delivered until the sheets are removed from the output tray.

\*\*9: Available staple positions vary depending on the paper size.

\*\*10: The Punch function requires the optional 2/4 Hole Punch Kit for Finisher-B or US 2/3 Hole Punch Kit for Finisher-B.

\*\*11: Available number of punch holes varies depending on the paper size.

\*\*12: Covers can be up to 220 gsm (Extra Heavyweight).

\*\*13: Inner connector within the body is excluded.

\*\*14: When installed on C3135, add 0.5 kg as cover.

\*\*15: Main Unit + Finisher-B4; When the paper support is pulled out and the Bypass Tray is fully extended.

### FINISHER- C4 WITH BOOKLET MAKER (OPTIONAL)

<b>Type</b>	<b>Output Tray</b> Sort (Offset available) / Stack (Offset available) <b>Finishing Tray</b> Sort (Offset available) / Stack (Offset available)
<b>Booklet Tray</b>	Sort / Stack
<b>Paper Size</b>	<b>Output Tray</b> Max: 12 x 19" (305 x 483 mm), A3; Min: A6, Postcard (100 x 148 mm) <b>Finishing Tray</b> Max: 12 x 19" (305 x 483 mm), A3; Min: A5 LEF
<b>Paper Weight</b>	<b>Output Tray</b> 52 to 300 gsm / 14 lb. bond to 111 lb. cover <sup>1</sup> <b>Finishing Tray</b> 52 to 300 gsm / 14 lb. bond to 111 lb. cover <sup>1</sup> <b>Output Tray</b> 500 sheets (A4) [Without Stapling] A4: 1500 sheets, JIS B4 or larger: 1500 sheets, A5 LEF: 1000 sheets, Mixed Size Stacking <sup>2</sup> : 300 sheets [With Stapling] A4: 200 sets or 1500 sheets JIS B4 or larger: 100 sets or 1500 sheets A5 LEF: 100 sets or 1000 sheets Mixed Size Stacking <sup>2</sup> : 70 sets or 200 sheets
<b>Paper Capacity<sup>2</sup></b>	<b>Booklet Tray</b> 20 sets <sup>4</sup>
<b>Capacity</b>	Staple: 50 sheets (90 gsm or less)
<b>Paper Size<sup>5</sup></b>	Max: A3, 11 x 17"; Min: A5 LEF
<b>Staple</b>	<b>Paper Weight</b> Staple: 52 to 300 gsm / 14 lb. bond to 111 lb. cover <b>Position</b> Single stapling, Dual stapling
<b>Punch<sup>6</sup></b>	<b>Number of Holes</b> 2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications) <b>Paper Size<sup>7</sup></b> Max: A3, 11 x 17"; Min: A5 LEF <b>Paper Weight</b> 52 to 220 gsm / 14 lb. bond to 122 lb. index <b>Capacity<sup>8</sup></b> Saddle Staple: 20 sheets (90 gsm or less) Single Fold: 5 sheets (90 gsm or less)
<b>Booklet Finishing</b>	<b>Paper Size</b> Max: SRA3 (320 x 450 mm), 12 x 18" (305 x 457 mm), A3; Min: JIS B5 <b>Paper Weight</b> Saddle Staple: 60 to 300 gsm / 16 lb. bond to 111 lb. cover Single Fold: 60 to 300 gsm / 16 lb. bond to 111 lb. cover
<b>Dimensions<sup>9</sup></b>	W 649 x D 692 x H 1054 mm / W 25.6 x D 27.3 x H 41.5" When Folder Unit CD3 is installed: W 888 x D 692 x H 1054 mm / W 35.0 x D 27.3 x H 41.5"
<b>Weight<sup>10</sup></b>	Finisher-C4 with Booklet Maker (w Punch): 57 kg / 126 lb. Folder Unit CD3: + 52 kg / 115 lb.
<b>Space Requirement<sup>11</sup></b>	[C4165/C4155/C3145]: W 1704 x D 790 mm / W 67.1 x D 31.1" When Folder Unit CD3 is installed: W 1938 x D 790 mm / W 76.3 x D 31.1" [C3135]: W 1704 x D 720 mm / W 67.1 x D 28.4" When Folder Unit CD3 is installed: W 1938 x D 720 mm / W 76.3 x D 28.4"

Note: Transport Unit is required.

Installation Kit required for use with Arivia C3135.

\*1: 52 to 55 gsm output paper may not be aligned properly depending on the paper type.

\*\*2: 70 gsm paper.

\*\*3: When larger size sheets are stacked on top of smaller size sheets.

\*\*4: When the output paper size is the same.

\*\*5: Available staple positions vary depending on the paper size.

\*\*6: Punching function cannot be added. Select a finisher with the hole punching function.

\*\*7: Available number of punch holes varies depending on the paper size.

\*\*8: The maximum number of sheets varies depending on the paper weight.

Booklet may not be tightly closed depending on the size or type of the paper.

\*\*9: Inner connector within the body is excluded.

\*\*10: When installed on C3135, add 1 kg as cover.

\*\*11: Main Unit + Finisher-C4 / Finisher-C4 with Booklet Maker; When the paper support is pulled out and the Bypass Tray is fully extended.

**FOLDER UNIT CD3 (OPTIONAL)**

<b>Z Fold Half Sheet</b>	<b>Paper Size</b>	A3, 11 x 17", JIS B4
	<b>Paper Weight</b>	60 to 90 gsm / 16 lb. bond to 24 lb. bond
<b>Tri-fold</b>	<b>Paper Size</b>	A4, Letter
	<b>Paper Weight</b>	60 to 90 gsm / 16 lb. bond to 24 lb. bond
	<b>Paper Capacity<sup>*1</sup></b>	40 sheets
<b>Power Supply<sup>*2</sup> / Maximum Power Consumption</b>		AC110 V +/- 10 %, 0.9 A, 60 Hz, 100 W AC220-240 V +/- 10 %, 0.6 A, 50/60 Hz common, 144 W
<b>Dimensions</b>		W 232 x D 588 x H 991 mm / W 9.2 x D 23.2 x H 39.1"
<b>Weight</b>		52 kg / 115lb.

Note: Option of Finisher-C4 / Finisher-C4 with Booklet Maker.

\*1: 70 gsm paper.

\*2: Power supply separate from the main unit is required.

**Arivia C3135, C3145, C4155, C4165**

**COLOR A3 MULTIFUNCTION PRINTER**

Katun's portfolio of Arivia color MFP's for large workgroups feature state-of-the-art technology that makes it easy to run your business and maximize productivity. Designed to integrate into any office environment, Arivia MFP's are designed to withstand today's security threats, offer an intuitive user experience, and deliver enhanced workflow solutions. Smartly designed for reliability and to minimize service calls, and with print speeds up to 65ppm, scan speeds up to 270ppm and a full range of input and finishing options, Arivia is powerful asset to your business.



For complete information on Katun products, please visit: [www.katun.com](http://www.katun.com)

© 2024 Katun. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

**KATUN®**

7760 France Ave. So. Suite 340  
 Minneapolis, MN 55435  
 1-800-328-2965 | [katun.com](http://katun.com)

