

#### **B-10-016 Series**

Rev. 6/04/24

### **Section 1: Identification**

#### **Product Identifier**

Trade Name: B-10-016 Series
Chemical Name: Polyurethane Resin

**Recommended Use:** Component for the manufacture of polyurethanes

**Restrictions on Use:** 

#### **Chemical Manufacturer Information**

 Name:
 NCFI Polyurethanes
 Phone:
 (800) 346-8229

 Address:
 1515 Carter Street, Mount Airy, NC 27030
 Fax:
 (336) 789-9586

Website: www.NCFI.com Emergency Phone: CHEMTREC: 800-424-9300

## **Section 2: Hazard Identification**

#### Classification of the substance or mixture

GHS Classification:			
Skin irritation, Category 3	Eye irritation, Category 2		

#### **GHS Labeling**

#### **Hazard Pictograms:**



#### Signal Word: Warning

Hazard Statements:			
•	May cause skin irritation.	•	May cause eye irritation.
•	May cause respiratory irritation.		

Pr	ecautionary Statements:		
•	Do not breathe fumes/gas/mist/vapors/spray.	•	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
•	Wear protective gloves/eye protection/face protection.	•	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
•	IF ON SKIN: Wash with plenty of soap and water.		

Other Hazards: None known.

## **Section 3: Composition**

Substance / Mixture:	Mixture.
----------------------	----------



### **B-10-016 Series**

Rev. 6/04/24

#### **Hazardous Components**

Name:	CAS#	Weight %
Trans-1-Chloro-3,3,3-trifluoropropene (CF <sub>3</sub> HC=CHCl or HFO-1233zd)	102687-65-0	5-15%
Tertiary Amine Catalysts	Proprietary	≤ 3 %
Trans-1,2-Dichloroethylene	156-60-5	≤ 3%

### **Section 4: First Aid Measures**

Inhalation:	Move to fresh air if symptoms develop. If breathing is difficult, give oxygen and call a physician.		
Eye Contact:	Flush with water for at least 15 minutes. See a physician if irritation develops.		
Ingestion:	Do not induce vomiting unless told to do so by a medical professional.		
Most Important symptoms and effects, acute and delayed:	May cause skin or eye irritation upon contact. Avoid breathing vapors. The dense vapors can displace and reduce breathing air in confined or unventilated spaces causing asphyxiation. Overexposure may cause tremors, confusion, irritation, and may result in cardiac sensitization.		
Indication of immediate medical attention and special treatment, if applicable:	N/A		
Skin Contact:	Wash with soap and water at first opportunity.		

## **Section 5: Fire-Fighting Measures**

Suitable extinguishing media:	Water, dry chemicals, CO <sub>2</sub> .	
Unsuitable extinguishing media:	None.	
Special hazards arising from the chemical:	Overheated containers may rupture due to pressure produced by CF <sub>3</sub> HC=CHCl. CF <sub>3</sub> HC=CHCl burns to form acids and noxious gases.	
Precautions for fire-fighters:	A self-contained breathing apparatus should be worn to protect against toxic and irritating vapors.	

### **Section 6: Accidental Release Measures**

Personal precautions, protective equipment, and emergency procedures:	Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.		
Environmental precautions:	Do not discharge into drains/surface waters/groundwater.		
Methods and material for containment and cleanup:	Absorb with sawdust, etc., and shovel into container. Waste material should be disposed of under conditions which meet federal, state, and local environmental regulations.		

## Section 7: Handling and Storage

Precautions for safe handling:	Store between 65°F and 85°F out of sunlight. Relieve pressure slowly when opening container. Under no circumstances should empty drums be burned or cut open with an electric or gas torch.	
Conditions for safe storage, including any incompatibilities:	Keep tightly sealed.	



#### **B-10-016 Series**

Rev. 6/04/24

### Section 8: Exposure Controls and PPE

### **Exposure Limits**

Component:	Type	Value
Trans-1-Chloro-3,3,3-trifluoropropene <sup>1</sup> ( CF <sub>3</sub> HC=CHCl or HFO-1233zd)	TWA	300 ppm recommended.
Tertiary Amine Catalysts <sup>1</sup>	N/A	None established.

<sup>&</sup>lt;sup>1</sup>Not listed as a carcinogen (NTA, IARC, OSHA).

### **Exposure Controls**

Respiratory Protection:	The specific respirator selected must be based on contamination levels of this material found in the workplace and the working limits of the respirator. A supplied air, full-face mask, positive pressure or continuous flow respirator or a supplied air hood is required when airborne concentrations are unknown or exceed threshold limit values. A positive pressure, self-contained breathing apparatus can be used in emergencies or other unusual situations. Full-face air purifying respirators equipped with organic vapor cartridges can be used in certain situations, see OSHA standard 29CFR 1910.134. All equipment must be NIOSH approved and maintained.
Hand, eye, skin, body protection:	Wear goggles or chemical safety glasses and chemically resistant rubber or plastic gloves. Avoid eye and skin contact. Eye wash system and showers should be available.

### **Section 9: Physical and Chemical Properties**

### Basic chemical and physical properties

Appearance:	Liquid.	Flammability:	N/A
Color:	Amber.	Upper/lower flammability or explosive limits:	N/A
Odor:	Ethereal odor.	Vapor pressure:	N/A
Odor threshold:	N/A	Vapor density:	N/A
pH:	N/A	Relative density:	1.15 g/mL
Melting pt/freezing pt:	<32°F	Solubility(ies):	Highly soluble in water.
Boiling pt/boiling range:	90°F	Partition coefficient (n-octanol/water):	N/A
Flash point:	>200°F	Auto-ignition temperature:	>500°F
Evaporation rate:	Slower than ether.	Decomposition temperature:	>500°F

# Section 10: Stability and Reactivity

Chemical stability:	Stable.	
Possibility of hazardous reactions:	N/A	
Conditions to avoid:	Temperatures of 85°F.	
Incompatible materials:	Isocyanates and other chemicals that react with hydroxyl groups.	
Hazardous decomposition	When burned, CO, CO <sub>2</sub> , NO <sub>x</sub> aliphatic fragments, halogens, halogen acids,	
products:	and possibly carbonyl halides.	



#### **B-10-016 Series**

Rev. 6/04/24

### Section 11: Toxicological Information

Acute toxicity:	May cause skin irritation.
Chronic toxicity:	Not available.
Likely routes of exposure:	Skin.
Symptoms related to physical, chemical and toxicological characteristics:	May cause skin irritation.
Delayed and immediate effects and chronic effects from short and long-term exposure:	May cause skin irritation. Avoid contact with eyes.
Numerical toxicity measures:	Not available.

## Section 12: Ecological Information

Ecotoxicity:	Not a marine pollutant.
Persistence and degradability:	No known significant effects.
Bioaccumulative potential:	Does not bioaccumulate.

### Section 13: Disposal

Waste disposal:	B component drums can be sent to drum reconditioners or disposed of as ordinary industrial	
	waste in compliance with pertinent regulations.	

## Section 14: Transport

UN number:	Not regulated.
UN Proper shipping name:	Not regulated.
Transport Hazard class(es):	Not regulated.
Packing group, if applicable:	Not regulated.
Marine pollutant:	No.
Special precautions:	None.

## Section 15: Regulatory

### Relevant safety, health, and environmental regulations

Inventory Status:	All components TSCA listed.
US Regulations:	No ingredients listed.
US Superfund Amendments and Reauthorization Act (SARA) Title III Section 313 information:	No ingredients listed.

## Section 16: Other

SDS First Issue Date:	07/29/20



### **B-10-016 Series**

Rev. 6/04/24

#### **IMPORTANT NOTICES**

This notification is a part of the Safety Data Sheet document and must not be detached. Any copying and redistribution of the Safety Data Sheet shall include copying of this notice and attaching the copy to the redistributed Safety Data Sheet copies.

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of NCFI. The data on this sheet relates only to the specific material designated herein. NCFI assumes no legal responsibility for use or reliance upon these data.